
HUMAN RESOURCES RESEARCH ORGANIZATION ALEXANDRIA VA F/G 5/9
PROJECT IMPACT SOFTWARE DOCUMENTATION: VI. VOLUME 2. ZEUS PROGR--ETC(U)
AUG 72 J GARNEAU, W UNDERSHILL, D SHUFORD DAHC19-73-C-0004
HUMRRO-RP-D1-72-5-VOL-2 AD-A055 023 UNCLASSIFIED OF 2 AD A055023



AD A 055023

August 1972 RP-D1-72-5



Project IMPACT Software Documentation: VI. Volume 2, Zeus Program Logic Descriptions

Research Product

by
Jean Garneau, William Underhill, and Doris Shuford

HumRRO Division No. 1 (System Operations)

Work Unit: IMPACT

Approved for public release; distribution unlimited.

HUMAN RESOURCES RESEARCH ORGANIZATION 300 North Washington Street • Alexandria, Virginia 22314

78 06 07 002 463

AD NO.

mul 2

UNCLASSIFIED SECURITY CLASSIFICATION OF THIS PAGE (When Date Entered) **READ INSTRUCTIONS** REPORT DOCUMENTATION PAGE BEFORE COMPLETING FORM REPORT NUMBER S CATALOG NUMBER RP-D1-72-RT & PERIOD COVERED TITLE (and Subtitle) PROJECT IMPACT SOFTWARE DOCUMENTATION: VI. VOLUME 2. ZEUS PROGRAM LOGIC DESCRIPTIONS. Research Product CONTRACT OR GRANT NUMBER(*) AUTHOR(A) Jean/Garneau, William/Undershill DAHC 19-73-C-0004 Doris/Shuford PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS PERFORMING ORGANIZATION NAME AND ADDRESS Human Resources Research Organization (HumRRO) 16 300 North Washington Street CDA Proj 20063101D734 Alexandria, Virginia 22314 12. REPORT DATE 11. CONTROLLING OFFICE NAME AND ADDRESS Aug Office, Chief of Research and Development Department of the Army 144 Washington, D.C. 20310 14. MONITORING AGENCY NAME & ADDRESS(If different from Controlling Office) 15. SECURITY CLASS Unclassified 15a. DECLASSIFICATION/DOWNGRADING 16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited. 17. DISTRIBUTION STATEMENT (of the ebstract entered in Block 20, if different from Report) 18. SUPPLEMENTARY NOTES Research performed by HumRRO Division No. 1 (System Operations), under Work Unit IMPACT.

19. KEY WORDS (Continue on reverse side if necessary and identify by block number)

Message Processing

Tasking

Cathode Ray Tube

Operating System (OS)

Command Processing

Time-Sharing

Memory Management

Queue Management

System Support

20) ABSTRACT (Continue on reverse side if necessary and identify by block number)

This research provides a description of Project IMPACT's time-sharing monitor ZEUS, which extends the capabilities of an IBM 360 or 370 computer system. Its functions, capabilities, structure and operation are discussed. ZEUS provides capabilities needed for real-time, interactive computer applications using cathode ray tube displays. This document is intended primarily for systems programmers, and is part of a series that will completely document the IMPACT software subsystem.

DD 1 JAN 73 1473

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE (When Date Entered)

August 1972 RP-D1-72-5

Project IMPACT Software Documentation: VI. Volume 2, Zeus Program Logic Descriptions

Research Product

by

Jean Garneau, William Underhill, and Doris Shuford

HumRRO Division No. 1 (System Operations)

Work Unit: IMPACT



HUMAN RESOURCES RESEARCH ORGANIZATION 300 North Washington Street • Alexandria, Virginia 22314

CONTENTS

		P
Introd	fuction	
	Organization of this Document	
	Overview	
Chapte		
1	System Modules	
	Section 1: Message Processing	
	Section 2: Command Processing	
	Section 3: System Support	
	Section 4: Initialization	
2	Macros	
	#ATTACH	
	#CALL	
	#CLOSEP	
	HE NEW MET CONTROL (1985) 이 전 10 10 10 10 10 10 10 10 10 10 10 10 10	
	#CONVRT	
	#COUNT	
	#DELETE	
	#DEQ	
	#ENQ	
	#FINDZVT	
	#FREEMEM	
	#GENSECT	
	#GETMEM	
	#GOTO	
	#LDREG	
	#LOAD	
	#LPSW	
	#MOVE	
	#OPENP	
	#QFB	
	#QUE	
	#REGS	
	#SET	
	#STIMER	
	#TTIMER	
	#WAIT	1
	#7FUSSVC	1

Chapter		Page
3	System Data Areas	109
	Section 1: Control Blocks and Tables	109
	Line Control Block	109
	Line Control Block-Overview	110
	Line Control Block-Detailed Description	111
	Queue Foundation Block	112
	Queue Foundation Block-Overview	112
	Queue Foundation Block-Detailed Description	112
	Zeus Terminal Control Block	113
	Zeus Terminal Control Block-Overview	113
	Zeus Terminal Control Block-Detailed Description	115
	Zeus Vector Table	117
	Zeus Vector Table-Overview	117
	Zeus Vector Table-Detailed Description	120
	Section 2: Queue Elements	121
	Core Queue Element	121
	Core Queue Element-Overview	121
	Core Queue Element-Detailed Description	122
	Load Request Element	122
	Load Request Element—Overview	122
	Load Request Element—Detailed Description	122
	Resource Queue Element	123
	Resource Queue Element-Overview	123
	Resource Queue Element-Detailed Description	123
	Timer Queue Element	123
	Timer Queue Element-Overview	123
	Timer Queue Element—Detailed Description	124
4	Utility Programs	125
5	Procedures	135
Figures		
1	Basic Zeus Structure	3
2	Summary, by Component, of Zeus Main Memory Requirements	4
3	Macro Coding Key	72
Tables		
1	Macros	71
2	Control Blocks	109

Project IMPACT Software Documentation: VI. Volume 2, Zeus Program Logic Descriptions

INTRODUCTION

This is the second volume in a two-volume set of documents describing Zeus, a time-sharing monitor for the IBM series 360 or 370 computer. In Volume 1, the nature, purpose, history, functions, and design concepts of Zeus are described; this document presents the program logic for Zeus subroutines and macros.

ORGANIZATION OF THIS DOCUMENT

Volume 2 is organized in five Chapters, as follows:

Chapter 1, "System Modules," describes each of the program modules in Zeus. The modules are grouped according to functions and these groups are presented in the sequence in which the functions are described in Volume 1.

Chapter 2, "Macros," describes the system macros provided by Zeus. These macros are used by Zeus subroutines and many are also suitable for application program use.

Chapter 3, "System Data Areas," identifies the structure and uses of control blocks and queue elements in Zeus.

Chapter 4, "Utilities," describes utility programs provided for the support of the Zeus system.

Chapter 5, "Procedures," lists the Job Control Language (JCL) procedures necessary for the implementation and operation of the Zeus system.

Program listings of Zeus modules and macros are available to the interested reader through HumRRO Division No. 1 (System Operations).

OVERVIEW

A brief description of how a terminal interacts with Zeus, as illustrated in Figure 1, will serve to place the Zeus components in proper perspective. In Figure 1, assume that the Zeus initialization routines have completed processing and a Terminal Task has been created for each terminal in the system. Each Terminal Task has issued a read to its terminal via OS and a Zeus macro. These functions are performed by the TERMIO component of Message and Command Processing. After initiating this operation, the Terminal Task waits for terminal input by entering the DSPTCHR component of System Support.

Eventually, the terminal initiates an input. At this time, OS notifies the Terminal Task associated with this terminal (via System Support) of the message availability. The Terminal Task, when activated, first determines if the message contains a command. If it does not it is routed to the external processor associated with this terminal.

If the message contains a command, the Terminal Task calls the Command Processing Subsystem to process it. (CMNDPR1 is the entry point to the Command Processing Subsystem.)


The Command Processing Subsystem interrogates the command and executes it as appropriate, utilizing Zeus macros and System Support for timer, queue, and memory management. Control Blocks are updated as necessary to maintain a state vector for the terminal.

Eventually Command Processing or the external processor will generate a request for output and subsequent input from the terminal, repeating the preceding operation.

A detailed description of this process can be found in Volume 1, Chapter 3, "Message Processing;" Chapter 4, "Command Processing;" and Chapter 5, "System Support Functions."

The main memory requirements for the major Zeus subsystems components are summarized in Figure 2. The reader may refer to the program description in subsequent chapters of this volume for detailed memory requirements for each Zeus module.

Basic Zeus Structure



^{*}Zeus Dynamic Memory used for transient routines, save areas, and queue extensions as well as I/O buffers.

^{**}Optional (non-Zeus) Component.

^{***}OS Dynamic Memory used for I/O Appendages, Open/Close/EOV, etc.

Summary, by Component, of Zeus Main Memory Requirements

Component		Main Memory*	
Message Processing		6K	
	EDITOR	3K	
Command	DIRECTOR	3K	
Processing	Status/control	2K	
	RJE	3K	
System Support		8K	
Buffer Pool	8K		
Control Bloo	2K		
OS Dynamic	5K		
Total		54K	

^{*}K = 1024 bytes of memory

Figure 2

Chapter 1

SYSTEM MODULES

This Chapter presents salient items of information regarding Zeus system modules. The system modules descriptions are organized alphabetically within sections, according to the type of function performed. These sections are presented in the sequence in which the functions are described in Volume 1. The subroutines are as follows:

Section 1: Message processing Section 2: Command processing Section 3: System support Section 4: Initialization

SECTION 1: MESSAGE PROCESSING

The program modules that perform message processing functions are shown in the following list:

Name	Function
CMF	I/O Communication Interface between a processor and a Terminal Task
CRTREAD	Request message from terminal
EMPTY	Request output to terminal
FULL	Process full output buffer condition
NTPIO	Initiate nonteleprocessing I/O operation
RESET	Acquire and initialize output buffer
RTERM	Terminal Task to Line Task interface for terminal input operation
RTERM1	Initiate terminal input operation
STACK	Format output buffer
TERM10	Terminal Task foundation module
WTERM	Terminal Task to Line Task interface for terminal output operation
WTERM1	Initiate terminal output operation

Zeus message processing concepts are described in Volume 1, Chapter 3. A description of each module follows.

CMF

FUNCTION:

Read/Write Communication Interface between a processor and

a Terminal Task.

INPUT:

R1 → BTAM Data Event Control Block (DECB)

R13 → 18-word save area

R14 → Return point address

R15 → Entry point to CMF

OUTPUT:

Updated DECB, TCB, and posted Terminal Task.

PROCESS:

The CMF routine is called by a processor to initiate a read or write operation on a remote terminal. CMF first interrogates the bytes at offset 36 of the DECB for an X 'FF' to determine if a terminal has been assigned to this DECB. If a terminal has been assigned, it loads the address of its TCB from bytes of the DECB and continues to the next step. Otherwise, it locates the Zeus Vector Table, gets the address of the TCB Queque from it, and scans the Queue for an available TCB. If one is found, its address is stored in bytes 37-39 of the DECB, the DECB address is stored in the TCB, and the next step is initiated. If a TCB is not available, the CMF returns to the caller. After the TCB belonging to this DECB is known, the address of the message to be output or the buffer to be used for input is moved from the DECB to the TCB. Editing is performed on outgoing messages as is required by specific processors. Finally, an ECB in the TCB is posted complete.

ZEUS MACROS USED:

#OPENP, #CALL, #GOTO, #LPSW, #COUNT, #CLOSEP, #GENSECT,

#FINDZVT

ROUTINES

CALLED:

SPIE, STAE

SIZE IN

BYTES:

403 bytes

EXTERNAL

REFERENCES:

ZEUSSVC, SPIE, STAE

EXIT:

Address in R14

ATTRIBUTES:

Serially Reusable

WRITTEN BY:

CRTREAD

FUNCTION:

Request input from terminal, process and, as appropriate,

return data to caller.

INPUT:

R12 + TCB

R13 → 18-word save area

R14 → Return point address

R15 → Entry point to CRTREAD

PROCESS:

CRTREAD is called by any routine that wants noncommand input from the terminal. CRTREAD first checks the current terminal output buffer to determine if it contains valid data. If it does, an output operation to the terminal is initiated by calling an output module, EMPTY. Upon return from EMPTY, or if the buffer contained no data, an input message from the terminal is requested via RTERM. Upon return from RTERM, CRTREAD waits on an ECB in its TCB for completion of the scheduled input operation. When the terminal responds, the message address is stored in the TCB and the ECB being waited on is posted by the Line Task associated with this terminal. When CRTREAD is dispatched, it checks the message for the presence of a Zeus command. If a command is located, the command processing subsystem is called. Upon return from this subsystem, a branch is made back to the first step of CRTREAD when the output buffer is checked for valid data. This loop will continue as long as the messages being input contain commands. When a message is input that does not contain a command, return is made to the original caller of CRTREAD.

ZEUS MACROS

USED:

#OPENP, #COUNT, #GOTO, #WAIT, #CLOSEP, #FREEMEM

ROUTINES

CALLED:

EMPTY, RTERM, CMNDPR1, STACK

SIZE IN

BYTES:

368 bytes

EXTERNAL

REFERENCES:

RTERM, GETSAVE, ICOUNT, EMPTY, FREEMEM

EXIT:

Address in R14

ATTRIBUTES:

REENTRANT

WRITTEN BY:

EMPTY

FUNCTION:

Request output operation to terminal.

INPUT:

R12 → TCB

R13 → 18-word save area

R14 → Return point address

R15 - Entry point to EMPTY

OUTPUT:

Output buffer, if any, written on terminal and deallocated.

PROCESS:

EMPTY is called to flush any valid data from the terminal output buffer. EMPTY first determines if, indeed, the buffer is available and does contain valid data. If not, it returns; otherwise it calls WTERM to schedule an output operation to the terminal. Upon return from WTERM, it waits on an ECB in the TCB for completion of the output operation. It then cleans up the TCB, frees the

buffer, and returns to the caller.

ZEUS MACROS

USED:

#OPENP, #GOTO, #SET, #WAIT, #COUNT, #CLOSEP, #FREEMEM

ROUTINES

CALLED:

WTERM

SIZE IN

BYTES:

316 bytes

EXTERNAL

REFERENCES:

WTERM, FREEMEM, GETSAVE, ICOUNT

EXIT:

Address in R14

ATTRIBUTES:

REENTRANT

WRITTEN BY:

FULL

FUNCTION:

Handle full output buffer condition

INPUT:

R12 → TCB

R13 + 18-word save area

R14 → Return point address

R15 → Entry point to FULL

OUTPUT:

Buffer output to terminal and then deallocated

PROCESS:

FULL first inserts a comment into Block One of the buffer explaining that the output operation is caused by a "full" CRT "page." The address of this block is available in the TCB. EMPTY then calls CRTREAD which schedules the output operation, waits for a "press-send", etc. CRTREAD returns a message that is discarded by FULL. FULL then

returns to the caller.

ZEUS MACROS

USED:

#OPENP, #COUNT, #CLOSEP, #FREEMEM

ROUTINES

CALLED:

CRTREAD

SIZE IN

BYTES:

168 bytes

EXTERNAL

REFERENCES:

GETSAVE, FREEMEM, ICOUNT

EXIT:

Address in R14

ATTRIBUTES:

REENTRANT

WRITTEN BY:

NTPIO

FUNCTION:

Initiate nonteleprocessing I/O operations.

INPUT:

R1 - I/O buffer plus operation code

R12 + TCB

R13 → 18-word save area

R14 + Return point address

R15 → Entry point to NTPIO

OUTPUT:

I/O operation scheduled

PROCESS:

NTPIO, using the Basic Access Method DECB contained in the TCB, initiates either an Input or an Output operation and then returns to the caller. Register 1 at entry contains the address of the buffer to be written from or read into. If register 1 is negative, the operation requested is a write, otherwise it is a read. If the first bit of the FILECB (in the TCB) byte is on, the I/O operation involves

keys, otherwise it is relative record I/O.

ZEUS MACROS

USED:

#OPENP, #GOTO, #COUNT, #CLOSEP

ROUTINES

CALLED:

None

SIZE IN

BYTES:

356 bytes

EXTERNAL

REFERENCES:

None

EXIT:

Address in R14

ATTRIBUTES:

Serially reusable

WRITTEN BY:

RESET

FUNCTION:

If a terminal output buffer is not currently available,

RESET allocates one and formats it.

INPUT:

R1 → TCB

R13 → 18-word save area

R14 → Return format address

R15 → Entry point to RESET

OUTPUT:

Updated TCB

PROCESS:

Reset checks SBUFIA in the TCB. If SBUFIA equals zero, a new

buffer is allocated via #GETMEM. The TCB fields SBUF1A, PAGELINE, PAGEND, LINEREM, and POSREM are updated and

control is returned to the caller.

ZEUS MACROS

USED:

#GENSECT, #OPENP, #GETMEM, #COUNT, #GOTO, #CLOSEP,

#REGS, #FREEMEM

ROUTINES

CALLED:

None

SIZE IN

BYTES:

264 bytes

EXTERNAL

REFERENCES:

GETSAVE, ICOUNT, DSPTCHR, GETMEM, FREEMEM

EXIT:

Address in R14

ATTRIBUTES:

REENTRANT

WRITTEN BY:

RTERM

FUNCTION:

To serve as an interface to the TP line task.

INPUT:

R12 → TCB

R13 - 18-word save area

R14 → Return point address

R15 → Entry point to RTERM

OUTPUT:

TCB and LCB updated to reflect current status.

PROCESS:

The user specifies the address of the TCB, which points to the terminal that is to be read. RTERM increments the poll count (LPOLLC) field of the line (LCB) to which the terminal belongs. If the line is idle, RTERM posts its LCB complete and returns. If the line is busy, return is made

without posting.

ZEUS MACROS

USED:

#OPENP, #REGS, #GENSECT, #SET, #GOTO, #CLOSEP

ROUTINES

CALLED:

None

SIZE IN

BYTES:

184 bytes

EXTERNAL

REFERENCES:

None

EXIT:

Address in R14

ATTRIBUTES:

Serially reusable

WRITTEN BY:

NAME: RTERM1 (Line Task Foundation Module)

To issue a read initial to the requesting line, move the FUNCTION:

message read to a buffer, and translate the message from

ASCII-8 to EBCDIC.

INPUT: R1 → LCB

R15 → Entry point to RTERM1

OUTPUT: TCBECB is posted complete (Byte 1 = X'40')

AIOBUF updated (only if return code = 0)

LSTAT updated LPOLLC updated

Error codes returned in right-most byte of TCBECB

00 = Read 0.K.

04,08,0C = Read bad, try again.

PROCESS:

RTERM1 is attached once for each communication line to be activated. It immediately branches to label "START". START interrogates the LCB to determine if any terminals (TCBs) require I/O servicing. If none do, the task enters idle mode by turning off the busy bit in the LCBFLGS byte of the LCB, and issuing a #WAIT on an ECB in the LCB. The task remains idle until a TCB associated with its LCB requests I/O by altering certain status fields in both the TCB and LCB and then posting the ECB that the task is waiting on.

When activated, the task first checks to see if a (terminal) output operation has caused the activation. If so, it branches to a routine (WTERM1) to take care of it/them. If not, it attempts to acquire memory for an input buffer. If not available, a #WAIT is issued to wait for the memory to become available. If the memory request is deleted during the wait, a branch is made back to START. When the memory is acquired, the address and length are saved and a read into the buffer is issued to the line. If it completes without error, the message is moved to a second buffer acquired in the same manner as the first, edited, and translated to EBCDIC. If the read completes with an error, the appropriate message is sent to the console, a write negative acknowledgement is issued, memory is freed, and a branch to START is issued. If the read completes with a negative response to poll, the negative response flag is turned on and a check is made to determine if all terminals requesting input have been polled. If not, the routine loops until all have been serviced. If all have been checked, the input buffer is freed and a branch is made to the write routine if any writes have been requested during the period. If no writes are pending, a #STIMER is issued and, when the interval completes, a branch to START is made.

ZEUS MACROS USED:

#SET, #REGS, #GENSECT, #OPEN, #GOTO, #GETMEM, #WAIT, #MOVE, #FREEMEM, #STIMER, #CALL

ROUTINES

CALLED:

WTERM1

SIZE IN

BYTES:

920 bytes

EXTERNAL REFERENCES: IECTTRNS, ITIMER, GETMEM, DSPTCHR, MOVEOOO, FREEMEM, ATE, WTERM1

EXIT:

To address in R14

ATTRIBUTES:

REENTRANT

WRITTEN BY:

STACK

FUNCTION:

To scan character string and format page for output to CRT.

INPUT:

RO = Maximum length of scan.

R1 -> Beginning of string to be scanned.

R12 + TCB

R14 → Return point

R15 → Entry point to STACK

OUTPUT:

Character string moved to output buffer and count of lines

and bytes remaining in page updated.

PROCESS:

The character string is scanned and the line count field in the TCB is decremented by one for each carriage return encountered or for each 84 bytes with no carriage return. The positions remaining field in the TCB is decremented by the length of the message. The scan is terminated when an ETX is found or when the scan limit (RO) is reached. The character string and prefix (if necessary) are moved to the output buffer, the address of which is in the SBUFIA field of the TCB. If the page is filled before the scan terminates, FULL and RESET are called prior

to continuing the scan.

ZEUS MACROS

USED:

#REGS, #OPENP, #GOTO, #SET, #COUNT, #CLOSEP

ROUTINES

CALLED:

RESET, FULL

SIZE IN

BYTES:

578 bytes

EXTERNAL

REFERENCES:

GETSAVE, RESET, FULL, ICOUNT, FREEMEM

EXIT:

Address in R14

ATTRIBUTES:

REENTRANT

WRITTEN BY:

TERMIO (Terminal Task foundation module)

FUNCTION:

INPUT:

R1 - Terminal Control Block

R13 + 18-word save area

R15 → TERMIO entry point address

OUTPUT:

Updated DECB, TCB, LCB; I/O operation initiated and

completed.

PROCESS:

TERMIO is attached by the Zeus initiation routine once for each terminal to be activated. It immediately waits on a "no work" ECB in the TCB passed to it during the attach. It remains dormant until its TCB has been acquired and posted by an external processor. When the TCB is posted by the external processor, the task becomes active. It loads the external processor DECB address into a register and checks the read/write flag. If it is a write operation, a buffer is acquired, the message is moved to it and translated, if necessary, to EBCDIC. Next, the message is checked to determine if a Zeus command is present. If a command is present, the Command Processing Subsystem is called, otherwise a routine (STACK) is called which handles message traffic to the terminal. If the operation requested is read, a routine (CRTREAD) is called which handles incoming messages from terminal. Upon return from this routine, an address is available in the TCB which points to the message to be passed to the external processor. TERMIO loads this address into a register, translates the

processor buffer, and posts the external processor's DECB. Finally, TERMIO again waits on its "no work" ECB.

#OPEN, #GENSECT, #SET, #WAIT, #GOTO, #COUNT, #LPSW, #CALL,

message, if necessary, moves the message to the external

#GETMEM, #FREEMEM

ROUTINES

USED:

ZEUS MACROS

CALLED:

MOVE, STACK, CRTREAD, EMPTY, CMNDPROC

SIZE IN

BYTES:

802 bytes

EXTERNAL REFERENCES:

MOVE, IECTTRNS, CMNDPROC, STACK, EMPTY, CRTREAD, DSPTCHR,

LTE, FREEMEM, CTLTAB, ETL, GETMEM

EXIT: N/A

ATTRIBUTES:

REENTRANT

WRITTEN BY:

WTERM

FUNCTION:

To serve as an interface between a Terminal Task and a

Line Task.

INPUT:

R12 → TCB

R13 → 18-word save area

R14 → Return point address

R15 → Entry point to WTERM

OUTPUT:

TCB and LCB updated to reflect current status.

PROCESS:

The user specifies the address of the terminal (address of the TCB) which is to be written. WTERM increments the write count field (LADDRC) of the line (LCB) to which the terminal belongs. If the line is idle, WTERM posts it complete and returns. If polling, WTERM calls RESETPL and then returns. If waiting for an interval to expire, a #TTIMER CNACEL is issued and then return is made. If waiting for memory, the memory queue element for this request is cancelled and return is made.

ZEUS MACROS USED:

#OPENP, #REGS, #SET, #GENSECT, #GOTO, #TTIMER, #FREEMEM,

#CLOSEP

ROUTINES

CALLED:

RESETPL

SIZE IN

BYTES:

304 bytes

EXTERNAL

REFERENCES:

ITIMER, RESETPL, FREEMEM

EXIT:

Address in R14

ATTRIBUTES:

Serially reusable

WRITTEN BY:

WTERM1

FUNCTION:

To issue an OS, write to a specified line.

INPUT:

R12 → TCB

AIOBUFF

→ buffer

BYTES 1&2 = buffer length BYTES 3&4 = message length BYTE 5 = X'02' (STX)

BYTES 6 to n = message

OUTPUT:

TCBECB posted complete (Byte 1 = X'40')

LSTAT updated LADDRC updated

Error codes in right-most byte of TCBECB

X'00' = no errors

X'04' = message too long for buffer
X'08' = no write operation initiated
X'0C' = write completed with error

PROCESS:

The message length and address are obtained from AIOBUF. The message is then translated from EBCDIC to ASCII-8, an ETX (X'03') placed in the last position of the buffer, and a STX $(X'\overline{0}2')$ in the first position to the buffer. A write initial with reset is issued, and if there was an error-free completion of the operation, the necessary LCB and TCB fields are updated. The TCBECB is posted with a O and return is made. If there was a non-X'7F' completion, an attempt is made to write a positive acknowledgement. If unsuccessful, a message is sent to the console, the TCBECB is posted with a 12, the necessary LCB and TCB fields are updated, and return is made. If the write "ack" is successful, the message is not sent but the TCBECB is posted with a 12, the LCB and TCB fields are updated, and return is made. If there was an error in the buffer length, the TCBECB is posted with a 4. If there was a buffer address error, a message is sent to the console and the TCBECB is posted with a O. If there was a bad write operation the TCBECB is posted with an 8.

ZEUS MACROS

USED:

#GENSECT, #OPENP, #GOTO, #WAIT, #SET, #CLOSEP, #REGS

ROUTINES

CALLED:

None

SIZE IN

BYTES:

464 bytes

EXTERNAL

REFERENCES:

IECTTRNS, GETSAVE, ETA, DSPTCHR, FREEMEM

EXIT:

To address in R14

ATTRIBUTES:

REENTRANT

WRITTEN BY:

SECTION 2: COMMAND PROCESSING

Zeus system modules that perform command processing functions are shown in the following list:

Name	Function
CMNDPR1	First-level command processing
CMNDPR2	Second-level command processing
SCAN	Scan and edit Zeus command strings
CON	Process console command
EOJ	Process LOG command
GCOUNT	Process counter status command
ICTBLID	Counter name table
RJE0000	First-Level Remote Job Entry (RJE)
RJE0100	Second-level .RJE
RJE0200	Third-level RJE
RJE0300	Fourth-level RJE
STA	First-level interface to all status commands
WTL	Write message to system log
WTO	Write message to operator console

Zeus command syntax and purpose are described in Volume 1, Chapter 4. A description of each module follows.

CMNDPR1

FUNCTION:

Process Zeus commands.

INPUT:

R1 -> First alpha character in command

R13 → 18-word save area

R14 → Return point address

R15 → Entry to CMNDPR1

OUTPUT:

Command is executed, appropriate error message is sent or appropriate transient routine loaded and branched to.

PROCESS:

First a check is made to see if a MODify is in process. If so, a return is made with a return code of 8. If not, SCAN is called and the command decoded. If it is a request for INFO, a branch is made to process INFO requests. If the command is POL, (), RJE, COR, or NOP a branch is made to the appropriate routines for processing these commands. For any other commands, CMNDPR2 is called to compile and insert CRT control information if necessary. Upon return, if the command was completely processed, immediate return is made. If an invalid verb was found by CMNDPR2, a branch is made to TRANLOAD to try to find the appropriate routine for processing the allegedly invalid verb. If unsuccessful, the appropriate error message is sent and return is made. If a valid command was incompletely processed by CMNDPR2, processing is completed within CMNDPR1--(CRE,COP,MOD,DEL). Return is made with a return code of 0 if processing was successfully completed and with a return code of 8 if not.

ZEUS MACROS USED:

#OPENP, #GENSECT, #GOTO, #SET, #CALL, #WAIT, #LOAD,
#DELETE, #CLOSEP, #REGS, #GETMEM, #FREEMEM #CONVRT, #MOVE

ROUTINES CALLED:

CMNDPR2, STACK, RJE0000, SCAN, EOJ, CONSOLE, SUBMIT, MSCHD,

CRTREAD, RESET.

SIZE IN

BYTES:

2998 bytes

EXTERNAL REFERENCES:

GETSAVE, DSPTCHR, IECTTRNS, FREEMEM, MOVEOOO, LDROOO,

GETMEM, SCAN, CMNDPR2, NTPIO, ATE, ÉMPTY, RESET, STACK, ETA, CRTREAD, SCANKEY, IFILE, CMNDPR1, SUBMIT, MSCHD, RJE0000,

STATUS, EOJ, CONSOLE, LTE, CNVTOOO.

EXIT:

Address in R14

ATTRIBUTES:

REENTRANT

WRITTEN BY:

CMNDPR2

FUNCTION:

Called by CMNDPR1 to complete processing of some Zeus commands and to compile and partially complete processing

of others.

INPUT:

R1 → Command left parenthesis

R13 → 18-word save area

R14 → Return point address

R15 → Entry point to CMNDPR2

AQWORK → Work area

OUTPUT:

Updated buffer and TCB

PROCESS:

The appropriate second-level subroutine is branched to, depending on the command being processed. The second-level subroutines decode the commands and turn on the appropriate bits in the TCB to indicate which command is being processed and whether the processing has been completed. Third-level routines are branched to if necessary to determine file and record, and to identify literals. Fourth-level routines are branched to, if necessary, to process literals and record keys. Fifth-level routines are branched to get next available buffer location. Each level of routines returns to the next higher level, eventually getting to the first-level routines which insert the appropriate prefix, set the return code, and return to CMNDPR1.

ZEUS MACROS

USED:

#OPENP, #REGS, #GENSECT, #GOTO, #CALL, #SET, #CLOSEP,

#FINDZVT, #FREEMEM, #CONVRT, #MOVE

ROUTINES

CALLED:

RESET, EMPTY

SIZE IN

BYTES:

2183 bytes

EXTERNAL

GETMEM, FREEMEM, ZEUSSVC, CNVTOOO, EMPTY, RESET, DFILE,

REFERENCES: RFILE, FFILE, IFILE, QFILE, SCANKEY

EXIT:

Address in R14

ATTRIBUTES:

REENTRANT

WRITTEN BY:

SCAN

FUNCTION:

To determine if a character string contains a Zeus command

and if so to edit it.

INPUT:

RO - Area in which to return SCANned command.

R1 → Beginning of character string

R12 → TCB

R13 → 18-word save area

R14 → Return address

R15 → Entry point to SCAN

OUTPUT:

Edited command in specified area, R1 → command terminator.

PROCESS:

The character string is scanned for the first nonblank character. If this character is not a left parenthesis, return is made. If it is a left parenthesis, the scan continues. If there are blanks, these are removed unless part of a literal. A literal is enclosed in balanced single quotes and is left as is unless it contains two consecutive single quotes, in which case one is removed. If unbalanced command delimiters or quotes are encountered, or the maximum length is exceeded, the appropriate message is sent to the terminal and the command is ignored.

ZEUS MACROS

USED:

#OPENP, #GENSECT, #COUNT, #GOTO, #CLOSEP, #REGS

ROUTINES

CALLED:

STACK

SIZE IN

BYTES:

726 bytes

EXTERNAL

REFERENCES:

GETSAVE, ICOUNT, FREEMEM, STACK

EXIT:

Address in R14

ATTRIBUTES:

REENTRANT

WRITTEN BY:

CON

FUNCTION:

Formats and outputs to the requesting terminal a copy of

the contents of the OS operator console buffers and

related information.

INPUT:

R11 - ZVT

R12 → TCB

R13 → 18-word save area

R14 → Return address

R15 → Entry point to CON

OUTPUT:

Formatted output buffer

PROCESS:

CON is a transient module invoked by CMNDPR1 as a result of a CON command. It stacks the following output for the requesting terminal:

- (1) Contents of the console input buffer.
- (2) Contents of the console output buffers.
- (3) List of outstanding replies by number and requesting task RB name.
- (4) List of tasks in dispatching priority order giving jobname, stepname, and active RB name.

ZEUS MACROS

USED:

#REGS, #OPENP, #GOTO, #CALL, #CLOSEP, #GENSECT

ROUTINES

CALLED:

STACK

SIZE IN

BYTES:

543 bytes

EXTERNAL

REFERENCES:

None

EXIT:

Address in R14

ATTRIBUTES:

REENTRANT, TRANSIENT

WRITTEN BY:

EOJ

FUNCTION:

Performs Zeus system shutdown functions.

INPUT:

 $R1 \rightarrow (E0J)$ command

R11 - ZVT

R12 → TCB

R14 → Return address

R15 → Entry point to E0J

OUTPUT:

None

PROCESS:

EOJ is a transient module invoked by an EOJ command from CMNDPR1. EOJ scans all TCBs in the system to determine if any ports are logged on. If ports are logged on, a message is stacked for the requester's terminal indicating that EOJ failed. If all ports are logged off, EOJ forces completion of the RDRINTPR's outstanding #STIMER and returns to CMNDPR1. The RDRINTPR then handles final EOJ processing.

ZEUS MACROS USED: #REGS, #OPENP, #GOTO, #CLOSEP, #SET, #TTIMER, #CALL,

#GENSECT

ROUTINES

CALLED:

STACK

SIZE IN

BYTES:

186 bytes

EXTERNAL

REFERENCES:

None

EXIT:

Address in R14

ATTRIBUTES:

REENTRANT, TRANSIENT

WRITTEN BY:

GCOUNT

FUNCTION:

Formats and writes on a terminal the contents of the

Zeus performance registers.

INPUT:

R11 → ZVT

R13 → 18-word save area

R14 → Return point address

R15 → Entry point to GCOUNT

OUTPUT:

GCOUNT calls STACK once for each nonzero counter value,

passing it a line of text containing a counter value and description from CSECT 'ICTBLID'.

ZEUS MACROS

USED:

#OPENP, #REGS, #COUNT, #GOTO, #CLOSEP, #CALL, #FREEMEM

ROUTINES

CALLED:

STACK

SIZE IN

BYTES:

408 bytes

EXTERNAL **REFERENCES:** ICOUNT1, ICOUNT2, GETSAVE, ICTBLID, ICTBL, ICTLGTH,

STACK, FREEMEM

EXIT:

Address in R14

ATTRIBUTES:

REENTRANT, TRANSIENT

WRITTEN BY:

ICTBLID

FUNCTION:

Driver for GCOUNT routine.

INPUT:

None

OUTPUT:

None

PROCESS:

Nonexecutable macro-operated table input to the $\ensuremath{\mathsf{GCOUNT}}$ routine.

ZEUS MACROS

USED:

None (internal macro).

ROUTINES

CALLED:

None

SIZE IN

BYTES:

266 bytes

EXIT:

N/A

ATTRIBUTES:

N/A

WRITTEN BY:

RJE0000

FUNCTION:

Performs the services requested by (RJE) 'text' commands.

INPUT:

R1 → (RJE text)

R12 → TCB

R13 → 18-word save area

R14 → Return point address

R15 → Entry point to RJE0000

OUTPUT:

R15 = 4 The input command has been replaced by a new

command to be executed.

R15 = 0 No new command has been created.

PROCESS:

RJE0000 is called by CMNDPR1 when an RJE command is

encountered. It examines the text portion of the command to determine which function is to be performed, and

branches to the appropriate routine.

ZEUS MACROS

USED:

#REGS, #GENSECT, #OPENP, #GOTO, #CALL, #WAIT, #ENQ, #DEQ,

#CLOSEP, #CONVRT

ROUTINES

CALLED:

STACK, NTPIO

SIZE IN

BYTES:

2488 bytes

EXTERNAL

GETSAVE, CNVTOOO, ETA, STACK, RFILE, NTPIO, DSPTCHR,

REFERENCES:

ENQCTRL, FREEMEM

EXIT:

Address in R14

ATTRIBUTES:

REENTRANT

WRITTEN BY:

William Underhill

RJE0100

FUNCTION:

RJE0100 is a resident module that handles the OS job sub-

mission function of the Zeus RJE subsystem.

INPUT:

R11 → ZVT

R13 → 18-word save area

R14 → Return point

R15 → Entry point to RJE0100

OUTPUT:

Updated job submission queue

PROCESS:

RJE0100 is attached as a Zeus task which waits on a #STIMER interval (currently set at 15 minutes). When the interval is completed (RJE0000 may force completion of the outstanding #STIMER in a VS system or upon encountering certain thresholds), RJE0100 loads and branches to RJE0200 which determines if any jobs have been placed in the Zeus RJE queue during the past interval. Upon return from RJE0200, a return code is checked to determine whether or not to load and execute REJ0300, which processes the job directory table created by RJE0200. Finally, RJE0100 checks a bit set by the EOJ processor (EOJ may force completion of the outstanding #STIMER). If the bit is not set, RJE0100 reissues the #STIMER and waits for the next interval to complete. If the bit is set, RJE0100 chains through the free queue elements in the Zeus memory subpool and returns them all to OS via a FREEMAIN macro and then issues an operator message requesting termination of Zeus.

ZEUS MACROS

USED:

#REGS, #GENSECT, #OPENP, #FINDZVT, #GOTO, #SET, #STIMER,

#DELETE, #LOAD.

ROUTINES

CALLED:

None

SIZE IN

BYTES:

552 bytes

EXTERNAL

REFERENCES:

ZEUSSVC, ITIMER, RFILE, RJEFILE, DSPTCHR, LDROOOO

EXIT:

N/A

ATTRIBUTES:

Attached Task

WRITTEN BY:

William Underhill

RJE0200

FUNCTION:

Creates a table of RJE text file pointers from the RJE job submission queue and resets the queue to empty status.

INPUT:

RO - Table of DECBs to be used in I/O processing.

R11 → ZVT

R13 → 18-word save area

R14 → Return point address

R15 → Entry point to RJE0200

OUTPUT:

R15 = 0 if queue was empty, or R15 = address of created table.

PROCESS:

RJE0200 #ENQs on the RJE text file to temporarily prevent updating of the submission queue by RJE0000. It then allocates a buffer and reads the submission queue record (Record 7) from the RJE text file. If the queue is empty, RJE0200 #DEQs and returns. If the queue is non-empty, a buffer equal to the size of the active part of the queue is allocated and the queue information is copied to the buffer. The queue size is then set to zero, the record is rewritten and RJE0200 #DEQs from the file and returns.

ZEUS MACROS USED: #REGS, #GENSECT, #OPENP, #ENQ, #WAIT, #GOTO, #DEQ,

#FREEMEN, #CLOSEP, #GETMEM

ROUTINES

CALLED:

None

SIZE IN

BYTES:

474 bytes

EXTERNAL

REFERENCES:

None

EXIT:

Address in R14

ATTRIBUTES:

Serially reusable, TRANSIENT

WRITTEN BY:

RJE0300

FUNCTION:

Reads, formats, and writes the submitted RJE file records into a partioned data set and starts an OS reader on the PDS member.

INPUT:

RO → Table of DECBs to be used for I/O

R1 -> Table of submitted RJE file record numbers

R11 → ZVT

R13 → 18-word save area

R14 → Return point address

R15 → Entry point to RJE0300

OUTPUT:

Batch jobs submitted to OS/VS Reader

PROCESS:

For each record given in the input table, RJE0300 does the following:

- (1) Translates record to EBCDIC
- (2) Scans for carriage return character
- (3) Moves line to 80-character output buffer and pads with blanks
- (4) If line is a job or exec card, writes line on operator console
- (5) Writes output buffer to PDS when full. When all records have been processed, RJE0300 calls the MSCHD routine with a "Start Reader" command specifying the PDS member just created.

ZEUS MACROS USED:

#REGS, #GENSECT, #OPENP, #GETMEM, #WAIT, #GOTO, #CALL,
#CLOSEP

ROUTINES CALLED:

MSCHD

SIZE IN

BYTES:

1,197 bytes

EXTERNAL

REFERENCES:

None

EXIT:

Address in R14

ATTRIBUTES:

Serially reusable, TRANSIENT

WRITTEN BY:

STA

FUNCTION:

Formats and outputs the contents of specified counters or

memory locations.

INPUT:

 $R1 \rightarrow (STAx)$

R11 → ZVT

R12 → TCB

R14 → Return address

R15 - Entry address to STA

OUTPUT:

R15 = 0 Normal return

R15 ≠ if error encountered

Formatted Buffer

PROCESS:

STA is a transient module loaded by CMNDPR1 in response to a STA command. The fourth character of the command determines the service to be performed as follows:

- (STAC) Outputs to the requesting terminal the contents of the Zeus system performance counters via the GCOUNT subroutine.
- (STAM) Outputs a specified portion of contiguous main memory locations in hex character and EBCDIC format.
- (STAZ) Outputs the Zeus Vector Table (ZVT) in (STAM) format.
- (STAT) Outputs the requesting terminals TCB in (STAM) format.
- (STAP) Outputs a list of log on names for the active ports on the system.

ZEUS MACROS

USED:

#REGS, #GENSECT, #OPENP, #GOTO, #CALL, #CLOSEP

ROUTINES

CALLED:

GCOUNT, CHTB, STACK

SIZE IN

BYTES:

630 bytes

EXTERNAL

REFERENCES: None

EXIT:

Address in R14

ATTRIBUTES:

REENTRANT, TRANSIENT

WRITTEN BY:

WTL

FUNCTION:

Sends messages to the WRITE-TO-PROGRAMMER log.

INPUT:

R1 → (WTL 'message')

R13 → 18-word save area

R14 → Return point address

R15 → Entry point to WTL

OUTPUT:

R15 = 0 normal return

R15 # if syntax error in command

Output message to Zeus SYSOUT listing

PROCESS:

The WTL process is identical to WTO except that, when the

OS WTO macro is executed, the MCSFLAGS field indicates

ROUTCDE = (11).

ZEUS MACROS

USED:

#REGS, #GOTO

ROUTINES

CALLED:

None

SIZE IN

BYTES:

228 bytes

EXTERNAL

REFERENCES:

None

EXIT:

Address in R14

ATTRIBUTES:

Serially reusable, TRANSIENT

WRITTEN BY:

WTO

FUNCTION:

Sends messages to the operator console

INPUT:

R1 → (WTO 'message')

R11 → ZVT

R13 → 18-word save area

R14 → Return point

R15 → Entry point to WTO

OUTPUT:

R15 = normal return

R15 # if syntax error in command

Output to operator console

PROCESS:

WTO is a transient routine invoked by CMNDPR1 when a WTO command is encountered. WTO scans the message contained in apostrophes, builds the list form of an OS WTO command, and executes it.

ZEUS MACROS

USED:

#REGS, #GOTO

ROUTINES

CALLED:

None

SIZE IN

BYTES:

208 bytes

EXTERNAL

REFERENCES:

None

EXIT:

Address in R14

ATTRIBUTES:

Serially reusable, TRANSIENT

WRITTEN BY:

SECTION 3: SYSTEM SUPPORT

The program modules that perform system support functions are listed as follows:

Name	<u>Function</u>
ATCHOO	Create Zeus Task
CHTB	Convert hexadecimal to binary
CNVT000	Convert numeric character to binary
CNTXCTL	Transfer control to 1 of 3 count modules
DSPTCHR	Schedule all Zeus tasks
ENQCTRL	Provide serialized access to any resource
FREEMEM	Release main memory
GETMEM	Acquire main memory
GETSAVE	Acquire a register save area
ICOUNT	Manipulate Zeus counter
ICOUNT1	Manipulate Zeus counter
ICOUNT2	Manipulate Zeus counter
ITIMER	Manipulate Zeus timer queue
LDR0000	First-level transient-load module
LDR0100	Second-level transient-load module
LDR0200	Third-level transient-load module
MOVE000	Move data within main memory
MOVE010	Move data and convert to hex within main memory
MSCHD	Interface to the Master Scheduler
PROB	Return task to problem program state
QUEMGR	Manipulate queue(s)
RCVRMGT	Process resource interlock condition
SCANKEY	Hash key
SUPV	Place task in supervisor state with protect key 0
TABLES	Translate tables (not executable module)

System support concepts are described in Volume 1, Chapter 5. A description of each subroutine follows.

ATCH00

FUNCTION:

Create A Zeus Task

INPUT:

RO - Address of routine to attach

R14 → Return address

R15 → Entry address to ATCHOO

OUTPUT:

Attached Task

PROCESS:

ATTCHOO is used via the #ATTACH macro to create a Zeus task. After making itself dispatchable, ATCHOO BALs to the specified routine. When this routine issues a #WAIT, the DSPTCHR will return control to ATCHOO which will, in turn, return control to the task that issued the #ATTACH. If the attached task returns, it will enter a subroutine of ATCHOO, which will then call the DSPTCHR with a special code so that the DSPTCHR will never again dispatch this

task.

ZEUS MACROS

USED:

#REGS, #COUNT, #GETMEM, #WAIT, #FREMEM

ROUTINES

CALLED:

None

SIZE IN

BYTES:

150 bytes

EXTERNAL

REFERENCES:

ICOUNT, GETMEM, DSPTCHR, FREEMEM

EXIT:

Address in R14

ATTRIBUTES:

Reentrant

WRITTEN BY:

J. Garneau

CHTB

FUNCTION:

Converts a hexadecimal character string to its equivalent

binary value.

INPUT:

RO = # of characters to scan (1-8)

R1 - Start of character string

R11 → ZVT

R13 → 18-word save area

R14 → Return point

R15 → Entry point to CHTB

OUTPUT:

RO = Binary value of field

Rl -> Input character at which processing terminated

R15 = 0 normal return

= 4 if scan limit (RO) is invalid

PROCESS:

CHTB scans the input string from low to high order positions. Each character must be an EBCDIC 0-9 or A-F. The character is converted to a binary value (0-15) and added to 16 times the previous cumulative value. Processing terminates when a non 0-9, A-F character is encountered or the scan limit

is reached.

ZEUS MACROS

USED:

None

ROUTINES

CALLED:

None

SIZE IN

BYTES:

148 bytes

EXTERNAL

REFERENCES:

None

EXIT:

Address in R14

ATTRIBUTES:

Serially reusable, TRANSIENT

WRITTEN BY:

CNVT000

FUNCTION:

Converts numeric character fields to binary.

INPUT:

R1 - Start of field

R13 → 18-word save area

R14 → Return address

R15 → Entry point to CNVT000

OUTPUT:

RO = Value of Field

R1 -> Nonnumeric which terminated the field

R15 = 0 if R0 is valid

0 if an error occurred

PROCESS:

CNVTOOO scans the input field for the first non 0-9 character, packs the resultant field, converts it to binary and returns to the caller.

ZEUS MACROS

USED:

#REGS

ROUTINES

CALLED:

None

SIZE IN

BYTES:

86 bytes

EXTERNAL

REFERENCES:

None

EXIT:

Address in R14

ATTRIBUTES:

Serially reusable

WRITTEN BY:

J. Garneau

CNTXCTL

FUNCTION:

To transfer control to ICOUNT, ICOUNT1 or ICOUNT2

INPUT:

R15 = base

1(R14) = code

Ø - go to ICOUNT
1 - go to ICOUNT1
2 - go to ICOUNT2

OUTPUT:

N/A

PROCESS:

The one-byte field at R14+1 is checked to determine to which routine control is to be transferred. The address of the appropriate routine is loaded into R15 and

branched to.

ZEUS MACROS

USED:

#GOTO, #REGS

ROUTINES

CALLED:

None

SIZE IN

BYTES:

52 bytes

EXTERNAL

REFERENCES:

ICOUNT1, ICOUNT2

EXIT:

To address in R15

ATTRIBUTES:

Serially reusable

WRITTEN BY:

J. Garneau

DSPTCHR

FUNCTION:

Distribute CPU cycles to all tasks active within the

ZEUS partition or region.

INPUT:

R1 -> ECB address list. Last entry in list has sign bit on

R13 → 18-word save area

R14 → Caller return point address

R15 → Entry point of DSPTCHR

OUTPUT:

ECB address list added to DSPTCHR stack if copy does not already exist there. First byte of first ECB address

modified to reflect status of list.

RØ = ECB posted.

R15 = Relative offset of posted ECB.

PROCESS:

Upon entry, the DSPTCHR first stores the callers' registers in the callers' save area, then checks the second bit of the control byte (first byte of the first ECB address in the passed list). If the bit is on, the list is already in the DSPTCHR stack. If the bit is off, the list is added to the stack and this bit is turned on.

The add operation is accomplished by scanning the list for a sign bit in an ECB address word, checking for adequate space in the stack, and then moving the list into the stack area. An entry is made in an associated stack that contains a count of the ECBs belonging to the task and the address of the task's source ECB list.

After the dispatcher is certain the ECB list is contained in the stack, it moves the first ECB from the source list to the first word of the caller's save area. The caller's save area address is then stored in the first word of the source ECB list, and the third bit of the control byte is set on to indicate that the caller is "dispatchable."

Dispatching is done on a "round robin" basis. Each entry to the DSPTCHR causes all ECBs in the stack to be checked for completion. The search always begins with the ECB following the last one dispatched. If the end of stack is reached before all ECBs are checked, the search is reinitialized to the top of the stack and continues until they are all checked.

When an ECB is posted complete the DSPTCHR searches the stack to locate it. It then retrieves this ECBs register save area, puts the address of the completed ECB in register 0, its offset into R15, reloads registers 0 to 14, and then branches to the address contained in register 14.

When the entire list has been searched without locating any completed ECBs, an OS WAIT macro is issued to the DSPTCHR ECB stack.

ZEUS MACROS

USED:

#GOTO, #SET, #COUNT

ROUTINES CALLED:

None

SIZE IN BYTES:

948 bytes

EXTERNAL

REFERENCES:

I COUNT

EXIT:

Address in R14

ATTRIBUTES:

Serially reusable

WRITTEN BY:

J. Garneau

ENQCTRL

FUNCTION:

Provide serialized access to any resource.

INPUT:

R1 → Resource Queue Element (RQE)

R1 > 0 IF ENQ Request

< 0 IF DEQ Request

R13 → 18-word save area

R14 → Return address

R15 → Entry address

OUTPUT:

R15 = 0 if caller was given control of the resource

R15 # 0 if the requested resource is currently in use

PROCESS:

#ENQ - The input RQE is added to a fifo ordered queue maintained by ENQCTRL. The queue is ordered by the second word of the RQE, which has been loaded with the resource name as specified in the #ENQ macro. R15 is set depending upon whether or not a previous RQE

with the same sort field (name) existed.

#DEQ - The specified RQE is removed from the queue. If the caller was first in the queue for the given resource (i.e., had control of the resource), and if the next queue entry specifies the same resource name, the second entry is given control. This is done by posting the ECB whose address is the third word of the RQE.

ZEUS MACROS

USED:

#FINDZVT, #REGS, #GENSECT, #GOTO, #QUE, #QFB

ROUTINES

CALLED:

None

SIZE IN

BYTES:

219 bytes

EXTERNAL

REFERENCES:

ZEUSSVC, QUEMGR

EXIT:

Address in R14

ATTRIBUTES:

Serially reusable

WRITTEN BY:

FREEMEM

FUNCTION:

To return memory to the ZEUS pool or to the OS pool

INPUT:

R1 → Memory to be freed

R1 - 4 = Size of memory to be freed

R14 → Return address

R15 → Entry address

OUTPUT:

Specified amount of memory at specified address freed

PROCESS:

The amount and address of the memory to be freed are obtained. If the memory belongs to the OS pool, a FREEMAIN is issued. If it belongs to the ZEUS pool, the associated queue elements are updated. If the memory to be freed is not on a double word boundary, an error message is sent to the console prior to completing the processing of the request. Next, the core queue is checked to see if any routines are waiting for memory. If so, the requests are satisfied, if possible, prior

to return.

ZEUS MACROS

USED:

#REGS, #GENSECT, #FINDZVT, #GOTO, #COUNT

ROUTINES

CALLED:

None

SIZE IN

BYTES:

576 bytes

EXTERNAL

REFERENCES:

ZEUSSVC, ICOUNT2, GETMEM

EXIT:

Address in R14

ATTRIBUTES:

Serially reusable

WRITTEN BY:

GETMEM

FUNCTION:

To obtain memory for use by ZEUS routines

INPUT:

R1 → CQE

,

RO = Amount requested

OUTPUT:

R14 → Return address

R15 → Entry address

PROCESS:

The size of the memory request is obtained. The ZPOOLA field of the ZVT is checked to see if the ZEUS pool is available. If so, the requested memory is gotten from the ZEUS pool. If unavailable the memory is gotten from the OS pool. If memory cannot be gotten--because none is available, a pool is exhausted, a limit reached, or because of a boundary error--an attempt is made to free a transient area to satisfy the request. If the memory is obtained, it is marked with the pool ID and the requester's ECB is posted.

1 040

ZEUS MACROS

USED:

#GOTO, #REGS, #GENSECT, #FINDZVT, #COUNT, #CALL

ROUTINES

CALLED:

QADD, LDR0200

SIZE IN

BYTES:

573 bytes

EXTERNAL

ZEUSSVC, ICOUNT, ICOUNT2, SUPV, LDRO200, QADD,

REFERENCES: ZMEM, PROB

EXIT:

Address in R14

ATTRIBUTES:

Serially reusable

WRITTEN BY:

GETSAVE

FUNCTION:

Acquire a save area, waiting for memory to become free

if necessary.

INPUT:

RO - Terminal control block (TCB) of active task

R1 - Size of requested save area in bytes

R11 + TCB

R13 → 18-word save area

R14 → Return address

R15 → Entry address to GETSAVE

OUTPUT:

R1 → Address of gotten memory

PROCESS:

GETSAVE is used in conjunction with the #OPENP macro when TYPE=RENT <u>and</u> TCBREG=n are specified. It handles and restores registers in a nonstandard manner. GETSAVE

executes a #GETMEM macro for the amount of memory

specified in R1, using a reserved save area (pointed to by the TCB) in order to wait for memory to become available

if necessary.

ZEUS MACROS

USED:

#GENSECT, #REGS, #COUNT, #GETMEM

ROUTINES

CALLED:

None

SIZE IN

BYTES:

104 bytes

EXTERNAL

REFERENCES:

ICOUNT, GETMEM, DSPTCHR

EXIT:

Address in R14

ATTRIBUTES:

Serially reusable

WRITTEN BY:

ICOUNT

FUNCTION:

Increments the specified ZEUS system performance

counter by 1.

INPUT:

 $R14 \rightarrow A$ one-byte field containing the counter number and return address - 4

R15 → Entry address

OUTPUT:

R15 = Current value of counter

PROCESS:

The counter number is checked against the range of available counters. If invalid, counter zero is used as an overflow counter. ICOUNT increments the specified

counter by 1 and returns to the caller.

ZEUS MACROS

USED:

#REGS, #GOTO

ROUTINES

CALLED:

None

SIZE IN

BYTES:

224 bytes

EXTERNAL

REFERENCES:

ICOUNT, ICOUNT2, ICOUNT1

EXIT:

Address in R14 + 4

ATTRIBUTES:

Serially reusable

WRITTEN BY:

I COUNT1

FUNCTION:

Adds a given number to the specified ZEUS counter.

INPUT:

R1 = Value to be added to counter

R14 - One-byte counter number and return address - 4

R15 → Entry address

OUTPUT:

R15 = Current value of counter

PROCESS:

Same as entry point ICOUNT, except that the value of R1 is added to the counter rather than adding a 1.

ZEUS MACROS

USED:

None

ROUTINES

CALLED:

None

SIZE IN

BYTES:

20 bytes

EXTERNAL

REFERENCES:

ICOUNT

EXIT:

Branches to ICOUNT

ATTRIBUTES:

Serially reusable

WRITTEN BY:

NAME: ICOUNT2 **FUNCTION:** Loads a given value into the specified ZEUS counter. INPUT: Same as ICOUNT1 OUTPUT: PROCESS: Same as ICOUNT1, except that the value in R1 is loaded into the counter rather than added. ZEUS MACROS USED: None ROUTINES CALLED: None SIZE IN BYTES: 20 bytes **EXTERNAL** REFERENCES: **I COUNT** EXIT: Branches to ICOUNT ATTRIBUTES: Serially reusable

WRITTEN BY:

ITIMER

FUNCTION:

To set, test, or cancel a timer interval, or force a previously set timer interval to 0.

INPUT:

R1 = Timer Queue Element (TQE)

RO = One of following codes:

0 - Add TQE to queue (#STIMER)

4 - Return interval remaining for this TQE (#TTIMER remaining).

8 - Remove TQE from queue (#TTIMER cancel)

12 - Force TQE completion by making current interval
 0 (#TTIMER complete)

R13 → 18-word save area

R14 → Return address

R15 → Entry address ITIMER

OUTPUT:

Timer Queue processed as specified.

PROCESS:

Upon initial entry, which is via an #ATTACH to create the task, a branch is made to ICOMP2. The initial branch instruction is NOPed. The address of the timer queue address word (QAW) is saved and R12, the base for IEXIT is saved. The following routines (which are documented below) are branch and linked to by this task which never terminates: ILAPSD, IPOST, IRESET. The completion bit in the ECB is turned off and IEXIT is BALed to to process any queued exits. The entire process is continuously repeated.

Upon any entry subsequent to the initial one ICOMP2 is not branched to. The TQE pointer and request type are saved. The address of the QAW is obtained. The following routines, (which are documented below), are BALed to: IDSBL, ILAPSD, IENBL. Upon return ITEST is branched to if the call was via the #TTIMER macro instruction. If the call was via #STIMER, IADD and IPOST are BALed to. Upon return, the completion bit in the ECB is turned off and IRESET and IEXIT are BALed to. Return is made to the address in R14.

IEXIT:

A test is made for any queued exits. If there are none, return is made. If any, a message is sent to the operator and the program terminates with an ABEND I, DUMP.

ITEST:

If the request is for the interval remaining IPOST is BALed to, the completion bit in the ECB is turned off, IRESET and IEXIT are BALed to, and return is made via

R14. If the request is to cancel or force to completion, the interval is set to 0, the ECB or EXIT address is saved, type = cancel is indicated, IPOST is branch and linked to, the ECB or EXIT address is restored, the ECB completion bit is turned off, IRESET and IEXIT are BALed to and return is made.

IDSBL:

The system mask is set to disable interrupts.

IENBL:

The system mask is set to enable interrupts.

ILAPSD:

This routine determines the amount of time that has elapsed since the interval timer was activated and returns this value in R6. If the interval timer is still active when this routine is called, it will be deactivated and the time left will be used in the computation.

IPOST:

The timer queue is gone through and each TQE with an interval remaining of 0 is dequeued. If the completion address is that of an exit address, it is queued on the exit queue; if it is an ECB address, the ECB is posted; if it is zero, no action is initiated, and the process continues. If the remaining interval is greater than 0, the next TQE is checked. When the end of the queue is reached, return is made via R11.

IADD:

This routine puts a TQE into the timer queue. The contents of R6 (elapsed time) are added to the TQE value (in timer units).

IRESET:

This routine obtains the address of the first TQE, if any on queue, saves the current interval, resets the interval timer (via STIMER macro), turns on the low order bit of the QAW, and returns.

I COMP:

This routine is entered from OS when the interval timer completes. The registers are saved, and the low order bit of the QAW is set to 0 to show that the timer is down. The time of day in timer units is obtained (via TIME macro) and saved. The timer ECB is posted complete to allow the timer to be restarted. The registers are restored, and return is made.

ZEUS MACROS

USED:

#REGS. #OPENP. #GOTO. #SET. #CLOSEP. #CALL. #COUNT. #WAIT

ROUTINES CALLED:

QADD, PROB, SUPV

SIZE IN

BYTES:

664 bytes

EXTERNAL REFERENCES: ICOUNT, SUPV, PROB, QADD, DSPTCHR

EXIT:

To address in R14

ATTRIBUTES:

Serially reusable

WRITTEN BY:

Jean A. Garneau

LDR0000

FUNCTION:

Called by the #LOAD macro to obtain the memory address of a transient module if available. Also called by #DELETE macro to relinquish control of a module.

INPUT:

RO → 8-byte name of module requested

R1 = Address of three-word load request block (LRB)

= 0 if no LRB specified with #LOAD macro

= 1 if called by #DELETE macro

R9 → TABENTRY Table

R13+ 18-word save area

R14→ Return address

R15→ Entry address

OUTPUT:

R15= Address of module if called by #LOAD

= 0 if module not available

= 4 normal return from #DELETE processing

= -1 if module not available and load request block was added to the queue of modules to be loaded.

Indicates that a #WAIT must be issued.

PROCESS:

#LOAD - LDROOOO seeks the requested name in a transient module table. If the module is available in memory, its responsibility count is incremented and the address is returned to the caller. If the module exists but is not available, the request is queued only if an LRB was specified with the #LOAD macro. A BLDL macro is issued on the ZEUS transient module PDS if the module is not found in the name table (i.e., for the first load). #DELETE - The module is found in the transient module table and its

responsibility count is decremented.

ZEUS MACROS

USED:

#REGS, #OPENP, #GOTO, #CALL, #CLOSEP, #COUNT, #QUE, #QFB

ROUTINES

CALLED:

QADD

SIZE IN BYTES: 1740 bytes

EXTERNAL

REFERENCES:

ICOUNT, TFILE, LRBQ, QUEMGR, LDRECB

EXIT:

Address in R14

ATTRIBUTES:

SERIALLY REUSABLE

WRITTEN BY:

W. Underhill

LDR0100

FUNCTION:

Loads requested transient modules into memory and posts

the associated requesting tasks.

INPUT:

R9 → TABENTRY Table

R13 → 18-word save area

R15 → Entry address

OUTPUT:

Loaded Modules

PROCESS:

LDR0100 is attached during Zeus initialization and immediately waits on a "no-work" ECB. When the no-work ECB is posted, LDR0100 de-queues the first LRB on the LRB chain, allocates memory for the module, issues a point macro on the transient file PDS, reads the module into memory, and posts the associated ECB with the module's address. The module's length and TTR are found in the transient module table. LDR0100 repeats this process for each LRB on the queue. When finished it waits on its no-

work ECB.

ZEUS MACROS

USED:

#REGS, #OPENP, #WAIT, #GOTO, #COUNT, #QUE, #QFB

ROUTINES

CALLED:

None

SIZE IN

BYTES:

472 bytes

EXTERNAL

REFERENCES:

ICOUNT, TFILE, DSPTCHR, GETMEM, FREEMEM, QUEMGR

EXIT:

N/A

ATTRIBUTES:

Attached Task

WRITTEN BY:

LDR0200

FUNCTION:

Frees the memory being occupied by one or all transient modules that are not currently in use.

INPUT:

R1 = 0 Free all unused modules

= n>0 Free the least recently used module of size

n or greater.

R9 → TABENTRY Table

R13 → 18-word save area

R14 → Return address

R15 → Entry address

OUTPUT:

R15 = 0 If memory freed

0 If no memory could be freed.

PROCESS:

LDR0200 scans the transient module table for modules with a zero responsibility count. If R1 = 0 the memory occupied by each such module is freed. If R1 = n>0 each unused module's size is checked. When the table scan terminates, the least recently used module (as indicated by a time stamp field) of sufficient size (if any) is freed.

ZEUS MACROS

USED:

#REGS, #GOTO, #FREEMEM

ROUTINES

CALLED:

NONE

SIZE IN

BYTES:

254 bytes

EXTERNAL

REFERENCES:

NUMMOD, MODTAB, FREEMEM

EXIT:

Address in R14

ATTRIBUTES:

SERIALLY REUSABLE

WRITTEN BY:

W. Underhill

MOVE000

FUNCTION:

MOVEOOD moves data (1 to 32767 bytes) from one location

to another.

INPUT:

RO → Source Area

R1 → Target Area

R14 → 2-byte length field, R14 + 2 → return address

R15 → Entry address to MOVE000

OUTPUT:

R1 = Address of last input byte + 1

R15 = 0 Normal return

R15 \neq 0 if input length <=0

PROCESS:

Data are moved, left to right, for the length specified.

ZEUS MACROS

USED:

#REGS, #GOTO

ROUTINES CALLED:

NONE

SIZE IN

BYTES:

100 bytes

EXTERNAL

REFERENCES:

NONE

EXIT:

Address in R14 + 2

ATTRIBUTES:

SERIALLY REUSABLE

WRITTEN BY:

J. Garneau

MOVE010

FUNCTION:

MOVE010 converts each input byte to two output hex

character bytes.

INPUT:

RO → Source Area

R1 → Target Area

R14 → 2-byte length field

R15 + 2 → return address

R15 → Entry address to MOVE010

OUTPUT:

R1 = Address of last input byte + 1

R15 = 0 normal return,

R15 = 4 if input length <2

PROCESS:

Each input byte is converted to its hexidecimal two-byte equivalent. These bytes are stored in the target area. The length specified is that of the target area. Consequently, the number of source area bytes converted is equal to one-half the length (in bytes) value specified. The length is rounded down, if necessary, to an even

number before conversion.

ZEUS MACROS

USED:

#REGS

ROUTINES

CALLED:

None

SIZE IN

BYTES:

156 bytes

EXTERNAL

REFERENCES:

None

EXIT:

Address in R14 + 2

ATTRIBUTES:

Serially Reusable

WRITTEN BY:

MSCHD

FUNCTION:

MSCHD passes commands to the OS or VS Master Scheduler.

INPUT:

R1 → Command

R13 → 18-word save area

R14 → Return address

R15 → Entry address to MSCHD

OUTPUT:

Command sent to OS or VS.

PROCESS:

The input string is scanned for an asterisk or ETX character, which defines the end of the string. MSCHD then enters supervisor state and protect key 0 and issues SVC 34 to pass the command to the Master Scheduler. If the sign bit is on in R1 at entry, the command is also written

on the operator's console.

(NOTE: Command must be of format '(//y*') where y is an

acceptable OS or VS command.)

ZEUS MACROS

USED:

#REGS, #OPENP, #LPSW, #CLOSEP

ROUTINES

CALLED:

None

SIZE IN

BYTES:

326 bytes

EXTERNAL

REFERENCES:

None

EXIT:

Address in R14

ATTRIBUTES:

Serially reusable, TRANSIENT

WRITTEN BY:

PROB

FUNCTION:

Returns the Zeus system to problem program state and

restores its assigned protect key.

INPUT:

R13 = Base

R14 → Return address

R15 → Entry address to PROB

OUTPUT:

Task in Problem State

ZEUS MACROS

USED:

#GOTO, #LPSW, #REGS

ROUTINES

CALLED:

None

SIZE IN

BYTES:

73 bytes

EXTERNAL

REFERENCES:

ZEUSSVC

EXIT:

Address in R14

ATTRIBUTES:

SERIALLY REUSABLE

WRITTEN BY:

W. Underhill

OUEMGR

FUNCTION:

QUEMGR is used to add/insert, delete, or locate an element

on a queue.

INPUT:

RO → Queue Foundation Block (QFB)

R1 - Element or, if ID specified, 4-character ID.

R14 → Argument and return address (-4)

R15 → Entry point to QUEMGR

OUTPUT:

R1 → Element deleted or located

Element chained onto queue if ADD, removed from queue if

DELETE.

R15 = Count of elements with identical ordering strings TYPE = (FIFO,ORDERED...) specified otherwise R15 not

relevant.

PROCESS:

The type of QFB is saved. A check is made to determine if the element to be processed is to go to either the top or bottom of an ordered queue. If so, the argument byte is saved. If the element is to be added to an unordered queue, a branch is made to this routine. The address of the last element on the queue is obtained from the QFB. The address of the previous element is obtained from the next address field of the last element. The address of the new element is stored in the last element field of the QFB and the previous last element address is stored in the new last element link word.

If the element is to be added to an ordered queue, bits 1 and 2 of the type field of the QFB are used to set the mask bits of a branch instruction that tests for a high or low compare condition. The queue to which the element is to be added is searched until equal IDs are found at which time it is determined whether it is a FIFO or LIFO operation. If FIFO, the element is added to the bottom of the queue of elements with the same ID; if LIFO, it is added to the top. In either case, the address chains are updated by storing the address of the next element in the current element and the address of the last element on the queue in the QFB.

If the element is to be located or deleted, a check is made to determine if the search is to be made on ID. If so, the proper pointer is adjusted and the search is conducted in the same manner as that for addition to an ordered queue. When the correct element is found, the chain address is updated by storing the address of the next element in the next address field of the previous element. The last element field of the QFB is updated if necessary.

If the search is to be made by element rather than ID, the queue is searched until the correct element is found, at which time it is deleted by updating the next element address field of the previous element and the last element field of the QFB if necessary.

Bits in the argument field and their meanings are as follows:

<u>Bits</u>	Argument
1	<pre>delete/locate ID equal delete/locate ID low delete/locate ID high</pre>
ii	delete/locate ID High delete/locate ID equal or low delete/locate ID equal or high
1 1 1 1.	<pre>delete/locate/add to top of queue delete/locate/add to bottom of queue delete locate ID specified</pre>

The structure of elements in all queues is as follows:

	word
Status	Link field
Ident	ification (optional)
Optional	data area (n bytes)

For details on individual fields see element descriptions by type in Chapter 3, Section 2.

The structure of all QFBs are as follows:

First element on q
Last element on qu
t Reserved
n

For details on the STATUS and TYPE fields, see Chapter 3, Section 1.

ZEUS MACROS

USED:

#REGS, #GOTO, #SET

ROUTINES CALLED:

None

SIZE IN BYTES:

354 bytes

EXTERNAL REFERENCES:

None

EXIT:

To address in R14 + 4

ATTRIBUTES:

Serially reusable

WRITTEN BY:

RCVRMGT

FUNCTION:

RCVRMGT attempts to diagnose and correct memory request

interlocks.

INPUT:

R13 → 18-word save area

R14 + return address

R15 → entry address of RCVRMGT

OUTPUT:

None

PROCESS:

RCVRMGT is attached as a Zeus task. It normally waits on an interval timer (currently set at 1 second). At the completion of each interval, when RCVRMGT gains control, it checks the memory wait queue. If the queue is empty, it reissues the #STIMER macro and waits for the next interval to complete. If the queue is non-empty, the first entry is checked for a X'FF' mark. If absent, RCVRMGT marks the entry with X'FF' and #STIMERS. If the mark is present, the queue entry has been on the queue since the last interval expired and a memory interlock is assumed to have occurred. RCVRMGT sets a bit indicating that the OS memory pool is to be used rather than the Zeus subpool and calls FREEMEM to attempt to allocate memory to the waiting tasks.

ZEUS MACROS

USED:

#OPENP, #REGS, #GENSECT, #FINDZVT, #STIMER, #GOTO, #COUNT,

#SET

ROUTINES

CALLED:

None

SIZE IN

BYTES:

316 bytes

EXTERNAL

REFERENCES:

ZEUSSVC, ITIMER, ICOUNT, DSPTCHR, LDR0200, FREEMEM.

EXIT:

N/A

ATTRIBUTES:

Serially reusable

WRITTEN BY:

SCANKEY

FUNCTION:

To hash a character string into a relative record number.

INPUT:

R1 → beginning of character string.

R13 → 18-word save area.

R14 → Return address.

R15 → Entry address to SCANKEY.

OUTPUT:

R15 = relative record number.

R1 → Edited character string used in hash operation.

PROCESS:

The input character string is scanned until an ETX is encountered or for a maximum of 40 bytes. All blanks and special characters are removed. The input character string is replaced with the edited character string (the KEY). The first four bytes of the key are logically added to the second four bytes and this total is logically added to the third four bytes. This number is made positive and divided by 1193. The result is the relative

record number that is loaded into R15.

ZEUS MACROS

USED:

#REGS, #OPENP, #CLOSEP

ROUTINES

CALLED:

None

SIZE IN

BYTES:

286 bytes

EXTERNAL

REFERENCES:

None

EXIT:

Address in R14

ATTRIBUTES:

Serially Reusable, TRANSIENT

WRITTEN BY:

D. Shuford

SUPV

FUNCTION:

Places the task in supervisor state, protect key zero

INPUT:

R13 - 18-word save area

R14 → Return address

R15 → Entry point

OUTPUT:

None

ZEUS MACROS

USED:

#REGS, #GOTO, #LPSW

ROUTINES

CALLED:

None

SIZE IN

BYTES:

56 bytes

EXTERNAL

REFERENCES:

ZEUSSVC

EXIT:

Address in R14

ATTRIBUTES:

Serially Reusable

WRITTEN BY:

W. Underhill

TABLES, ENTRY-ETL, LTE, ATE, ETA

FUNCTION:

To provide translate tables for use by Zeus routines.

The tables provided are:

ETL EBCDIC to 1050 line code. LTE 1050 line code to EBCDIC.

ATE ASCII to EBCDIC. ETA EBCDIC to ASCII

CTLTAB

The tables have been modified as follows:

ETL

Upper case letters changed to lower case.

Carriage return changed to null.

Horizontal tab changed to restore.

Vertical tab changed to bypass.

Home changed to end of addressing.

End of transmission changed to end of block.

End of test changed to end of block.

Dot (.) changed to space.

Back slash changed to reader stop.

Up arrow changed to punch on.

Left arrow changed to punch off.

LTE

Lower case letters changed to upper case.

End of addressing changed to null.

End of block changed to end of text.

Space changed to dot (.).

Idle changed to idle (ASCII).

Bypass changed to idle.

Restore changed to idle.

Null changed to carriage return.

Reader stop changed to back slash.

Punch on changed to up arrow.

Punch off changed to left arrow.

All modifications (LTE) are made to both upper and lower case control characters.

INPUT:

N/A

OUTPUT:

N/A

PROCESS:

N/A

ZEUS MACROS

USED:

None

ROUTINES CALLED:

None

SIZE IN BYTES:

1,024 bytes

EXTERNAL

REFERENCES:

None

EXIT:

N/A

ATTRIBUTES:

Read Only

WRITTEN BY:

Doris Shuford

SECTION 4: INITIALIZATION

The Zeus initialization programs are presented in the following list:

Nam	<u>ie</u>	Function
INI	то	Open files, load external processors, and link to INIT1
INI	T1	Process Zeus parameter cards, attach tasks, create control blocks, and transfer control to INIT2
INI	Т2	Create Zeus main memory pool and return control to INITO

The initialization process is described in Volume 1, Chapter 6. A description of each subroutine follows.

NAME:

INITO

FUNCTION:

First-level Zeus initiation.

INPUT:

R1 → External Processor Name

R13 → 18-word save area

R14 → Return point address

R15 → Entry point address to INITO

OUTPUT:

Open files, and loaded external processor(s).

PROCESS:

INITO first interrogates the parm field as passed via register 1. If a name is present, it is assumed to be an external processor name and an attempt is made to load it. If no external processor is requested, a dummy external processor is loaded. INITO then obtains the address of the ZVT and from it gets a list of DCBs to open, which it does next. Finally, it links to INIT1. Upon return, INITO initializes the external processor(s).

ZEUS MACROS

USED:

#OPENP, #GENSECT, #GOTO, #LPSW, #COUNT, #CLOSEP, #FINDZVT,

#SET, #WAIT

ROUTINES

CALLED:

None

SIZE IN BYTES: 1,704 bytes

EXTERNAL

REFERENCES:

ICOUNT2, DDMOSNO1, GETSAVE, ZEUSSVC

EXIT:

Address in R14

ATTRIBUTES:

REENTRANT

WRITTEN BY:

J. Garneau

NAME:

INITI

FUNCTION:

Read Zeus parameter cards and create control blocks, and ATTACH tasks which will be required for operation.

INPUT:

R1 → parameter list

R13 → 18-word save area

R14 → return address

R15 → Entry point to INIT1

Zeus parameter cards

OUTPUT:

The following tasks ATTACHed:

ZITIMER - interval timer (1)
ZRJE0100 - reader interpreter (1)

ZWTROOO - writer (1)

ZRCVRMGT - recovery management (1) ZLDR0100 - transient loader (1) ZLINEIO - line (1 per line)

ZTERMIO - terminal (1 per terminal)

The following control blocks created:

TCB - Task control block (1 per terminal)
LCB - Line control block (1 per line)
PAL - Polling/Addressing list (1 per line)

PROCESS:

SYSIN is OPENed and the required tasks ATTACHed. The parameter cards are read and the amount of main storage to be RESERVED, ALLOCATED, or LIMITED is determined. This value is stored in the ZPOOLA field of the ZVT. The line and terminals that are to be used are determined and the necessary control blocks created. When all parameter cards have been processed SYSIN is CLOSED and control is transferred to INIT2.

ZEUS MACROS

USED:

#OPENP, #GENSECT, #REGS, #FINDZVT, #WAIT, #LPSW, #GOTO,

#ATTACH, #SET, #GETMEM

ROUTINES

CALLED:

None

SIZE IN

BYTES:

1,832 bytes

EXTERNAL

REFERENCES:

None

EXIT:

INIT2

ATTRIBUTES:

Serially reusable

WRITTEN BY:

Jean Garneau

NAME:

INIT2

FUNCTION:

Determines the type of memory allocation scheme to be used

by Zeus.

INPUT:

R1 → parameter list

R13 → 18-word save area

R14 → Return address

R15 → Entry point to INIT2

OUTPUT:

ZPOOLA field of ZVT updated.

PROCESS:

ZPOOLA word of the ZVT is interrogated. If ALLOCATE was specified, memory is acquired and structured into a Zeus Pool. If RESERVE was specified, memory is reserved for OS and what remains is structured into a Zeus Pool. If LIMIT or no parameters was specified, no Zeus Pool is structured. The ZPOOLA word of the ZVT before and after INIT2 is as

follows:

Before:

Byte 1 bit O ALLOCATE

1 RESERVE 2 LIMIT

. 2 L

Bytes 2-4 value

After:

Byte 1 bit 0 No Zeus Pool

bit 1 Limit specified

Bytes 2-4

Address of Zeus pool or limit value

or zero.

ZEUS MACROS

USED:

#OPENP, #REGS, #FINDZVT, #GOTO, #CLOSEP, #SET

ROUTINES

CALLED:

None

SIZE IN

BYTES:

396 bytes

EXTERNAL

REFERENCES:

ZEUSSVC

EXIT:

Address in R14

ATTRIBUTES:

Serially reusable

WRITTEN BY:

Jean Garneau

Chapter 2

MACROS

Several macros have been created to reduce the amount of detail coding required to use Zeus functions. A number of these macros can be considered general purpose since they may be used in any environment. Some may be used after careful consideration of the effect of execution, and some may be used only within a system built on Zeus components and architecture.

A summary listing of available macros is contained in Table 1. Column 3 of the table indicates the level of utility of the individual macros. The symbols and notations used to represent macro syntax are presented in Figure 3. A description of each macro follows.

Table 1
Macros

Name	Function	Use ^a
#ATTACH	Create a Zeus Task	3
#CALL	Call a subroutine	1
#CLOSEP	Close program and return to caller	1
#CONVRT	Convert data from one format to another	1
#COUNT	Accumulate statistics	2
#DELETE	Delete Transient Module	3
#DEQ	Release resource from exclusive control	2
#ENQ	Acquire resource for exclusive control	2
#FINDZVT	Locate Vector Table	2
#FREEMEM	Release main memory	2
#GENSECT	Generate Label Map	3
#GETMEM	Acquire main memory	2
#GOTO	Execute conditional branch	1
#LDREG	Load register	1
#LOAD	Load transient module	3
#LPSW	Load program status word	2
#MOVE	Move data with/without translate	1
#OPENP	Open program	1
#QFB	Generate queue foundation block	1
#QUE	Process Queue	1
#REGS	Register symbol generation	1
#SET	Set bit(s) on/off/invert	1
#STIMER	Set interval timer	2
#TTIMER	Test interval timer	2
#WAIT	Wait for event completion	3
#ZEUSSVC	Execute Zeus SVC	2

^a1 = General Use

^{2 =} Restricted Use

^{3 =} Zeus only

Macro Coding Key

Meaning
Code exactly as shown.
Replace as instructed.
Optional argument.
Select one option from stack. An underlined option will be defaulted if the argument is omitted. If no option is underlined, the argument cannot be omitted unless the entire argument is enclosed within brackets.
Any address valid in an 'LA' instruction; a symbol valid in an 'A' or 'V' type address constant; or (r), $2 \le r \le 12$, given the address is available in the register specified.
Any symbol valid within an 'A' or 'V' type address constant.
General purpose register 0-15 enclosed within parentheses.
General purpose register 2-12, parentheses optional.
One or more alphanumeric characters.

Figure 3

#ATTACH

#ATTACH -- Create a Zeus Task

The #ATTACH macro provides a facility whereby one task can create another task.

[labe]	#ATTACH	{EPADDR=address name—char (r)	[,PARAM=address]
--------	---------	-------------------------------------	------------------

label

specifies the address of the first executable instruction generated by the macro.

EPADDR=address

the address of a word in main storage where the address of the routine being attached is stored.

name

code a character string from 1 to 8 characters which identifies the routine to be attached. The name must satisfy the requirements of a V-type address constant.

(r)

replace r with a register that has previously been loaded with the address of the routine being attached.

PARAM=address

The address that will be passed to the attached task via register 1. If omitted, register 1 will be passed unaltered.

Registers Altered: 0, 14 and 15 External References: ATCHOO

#CALL -- Call subroutine

The #CALL macro provides a mechanism for transferring control to another module.

[label]	#CALL	{EPADDR=address name-char [, RESOLVE=LOCAL]}
---------	-------	--

label

specifies the address of the first executable instruction generated by the macro.

EPADDR=address

The address of a word in main storage where the address of the routine being called is stored.

name-char

code a character string from 1 to 8 characters which identifies the routine to be called. The name must satisfy the requirements of a V-type address constant.

RESOLVE=LOCAL

code this parameter to override the effect of the 'RESOLVE=#CALL' parameter of the #GENSECT macro. The override is in effect during the expansion of this macro only. If the #GENSECT macro option has not been selected during this assembly, 'RESOLVE=LOCAL' is the default. For additional details see the #GENSECT macro description in this document.

(r)

replace r with a register that has previously been loaded with the address of the routine being called.

Registers Altered: 14, 15 Written by: J. Garneau #CLOSEP -- Close Program/Subroutine and Return to Caller

The #CLOSEP macro release save areas, 1 restores all (0-15) registers, and returns to the caller.

[label]	#CLOSEP	$[RC = \begin{cases} value-char \\ (r) \end{cases}] [,RET = \{ \frac{yes}{no} \}] [,SAREA = address]$
---------	---------	---

label

 $\ensuremath{\mathsf{specifies}}$ the label of the first executable instruction generated by the macro.

$$RC = \begin{cases} value \\ (r) \end{cases}$$

a value (0 to 4095) or a register that contains a value $(\pm 2^{32-1})$ that will be loaded into register 15 before return is made. If omitted, return is made with register 15 unaltered.

$$RET = \left\{ \frac{YES}{NO} \right\}$$

If YES is coded or the parameter omitted, an unconditional branch to the address contained in register 14 will be made after SAVE areas have been freed, and registers 0--15 are restored. If NO is coded, no branch will be made.

SAREA=address

The address of the save area from which registers 0-15 should be loaded. Registers are loaded, 14 through 12, starting with the third

¹Save areas dynamically acquired by the #OPENP macro will be freed automatically by #CLOSEP. The size of the save area freed in such a case is determined by the #OPENP, which physically precedes this #CLOSEP in the assembly not the #OPENP, which may possibly precede it "logically."

word of the save area. If this parameter is omitted, the address of the save area from which the registers are to be loaded is assumed to be stored in a word that is addressed by adding 4 to the current contents of register 13 (note: this is standard OS convention and is compatible with the #OPENP macro).

Registers Altered: See 'RC=' option Written by: J. Garneau

#CONVRT


#CONVRT -- Convert Data From One Format to Another

The #CONVRT macro instruction is used to reduce numeric character strings of unknown length to binary values or to expand binary values to "edited" numeric character strings.

Convert to binary requires a character string address and a scan limit value. The character string is scanned left to right (within the limit imposed) for a nonblank character. The scan continues from that point until either a nonnumeric character is encountered or until the scan limit value equals zero. The character string so delimited is then used as input to the conversion routine.

Upon return, register 15 will equal zero, register 0 will contain the converted number, and register 1 will contain the address of the character that terminated the scan. If during the scan or conversion it is determined that the string is less than 1 character or greater than 15 characters in length, or the resultant value is larger than 2,147,483,647, return will be made with register 15 equal to 4, 8, or 12 respective?

Convert to character converts a binary value to an EBCDIC character string equivalent. Upon return, general register 1 points to a '+' or '-' followed by a string of digits equivalent to the (input) binary value. General register 0 contains a count of the number of digits in the string. Nonsignificant zeroes are edited out except when the input value is 0. In such a case, register 1 will point to '+0' and register 0 will equal 1.



address

is the address in main storage of the data to be converted. If this argument is omitted, general purpose register 1 is assumed to contain the address.

register

specifies the general purpose register that contains the number to be converted. If this argument is omitted, register 0 is assumed to contain the number.

TO-BIN

convert from character to binary

TO-CHA

convert from binary to character

limit

specifies a number equal to or less than 4095 (or a register, r, which contains a number) to limit the scan. If omitted, a limit of 4095 is assumed. If the limit is contained in a register, the register, upon return, will be reduced by an amount equal to the number of bytes scanned.

Registers Altered: 0, 1, 14, 15 External References: CNVTO00 or CNVTO10

#COUNT -- Accumulate Statistics

The #COUNT routine is used to add, subtract, or load data into a series of full word counters. Upon return from a #COUNT, register 15 will contain a number equivalent to the current value of the specified counter.

	[label]	#COUNT	counter-char	Γ,	LOAD	}=	value-char	}
--	---------	--------	--------------	----	------	----	------------	---

label

specifies the address of the first executable instruction generated by the macro.

counter-char

code a number from 1 to 255 to specify the counter to be affected. If a counter does not exist that can be associated with this number, a special counter (counter 0) will be assumed.

$${DD} = {value-char \choose r}$$

code a number from 1 to 4095 or replace r with a register that has previously been loaded with a number $(\pm 2^{-31})$. The number is loaded into the specified counter or is added to the current value of the specified counter depending on which keyword is coded. If both these keywords are omitted, the specified counter will be incremented by one (1).

Registers Altered: 1, 14, 15

External References: ICOUNT or ICOUNT1 or ICOUNT2 or CNTXCTL

#DELETE

#DELETE -- Delete Transient Module

The # DELETE macro provides a facility whereby a task can delete a module that had previously been loaded with a # LOAD macro.

[label]	#DELETE	EP={address 'char'}
---------	---------	------------------------

labe1

The address of the first executable instruction generated by the $\mbox{\it macro}$.

EP={address | char'}

The address of an 8-byte character string (padded with blanks if necessary) or a 1- to 8-byte character string enclosed in single quotes that identifies the module to be deleted.

Registers Altered: 0, 1, 14, 15 External References: LDR0000 Written by: J. Garneau #DEQ -- Release Resource From Exclusion Control

The #DEQ macro enables a task to release a resource that it has exclusive control of.

-	[label]	#DEQ	[RQE=address]

label

The address of the first executable instruction $generated\ by\ the\ macro.$

RQE=address

The address of the RQE that was specified in the #ENG macro instruction issued to gain control of the specified resource. If omitted, register 1 is assumed to contain the address of the RQE.

Registers Altered: 1, 14, 15 External References: ENQCTRL Written by: J. Garneau #ENQ -- Request Exclusive Control of Resource

The #ENQ macro provides a facility whereby a task may request exclusive control of a resource.

	[label]	#ENQ	[NAME=	address 'char'][,ECB=address][RQE=address][,WAIT=address]
--	---------	------	--------	-------------------	---

label

The address of the first executable instruction generated by the \max of

The address of a 4-byte character string (padded with blanks if necessary) or a 1- to 4-byte character string enclosed in single quotes. If omitted, the character string is assumed to have been stored in bytes 4-8 of the RQE.

ECB=address

The address of the ECB to be posted complete when exclusive control of the resource is acquired. If omitted, the ECB address is assumed to have been stored in bytes 8-12 of the RQE.

RQE=address

The address of the Resource Queue Element used to process the #ENQ request. The RQE must be at least three words long. If omitted, Register 1 is assumed to contain the address of the RQE.

WAIT=address

The address of the ECBLIST that contains the address of the ECB that will be posted when the task gains exclusive control of the

requested resource. If omitted, no automatic wait is generated within the #ENQ macro. It is possible for the task to #WAIT on this list at any latter point so long as the integrity of the RQE is honored.

Registers Altered: 0, 1, 14, 15 External References: ENQCTRL Written by: J. Garneau

#FINDZVT

#FINDZVT -- Locate the Zeus Vector Table

The #FINDZVT macro returns to the caller with the address of the ZVT (Zeus Vector Table) in register 15.

[label] #FINDZVT

label

specifies the address of first executable instruction generated by the macro.

Registers Altered: 0, 1, 14, 15 External References: ZEUSSVC

#FREEMEM

#FREEMEM -- Free Main Memory

The #FREEMEM macro provides a means for freeing main memory previously acquired via a #GETMEM macro.

[label] #FREEMEM [address]

labe1

The address of the first executable instruction generated by the macro.

address

The address of the memory segment to be freed. The memory segment must have previously been allocated with a #GETMEM macro. If omitted, Register 1 is assumed to contain the memory segment address.

Registers Altered: 1, 14, 15 External References: FREEMEM Written by: J. Garneau

#GENSECT

#GENSECT -- Generate DSECT/CSECT

The GENSECT macro provides a means of generating DSECTS (or CSECTS) which map Zeus blocks and tables.

#GENSECT type [,BASE=register] [,RESOLVE=#CALL]

type

code LCB to generate a Line Control Block DSECT, TCB to generate a Task Control Block DSECT, ZVT to generate a Zeus Vector Table DSECT, or DSKREC to generate a Text File Header DSECT. In each case the name of the DSECT will be its type (e.g., LCB DSECT).

BASE=register

code any register notation valid in a 'USING' instruction. If omitted, no base register will be assigned to the DSECT generated.

RESOLVE=#CALL

code in a ZVT generation request to cause the addresses of routines referenced by a #CALL macro to be obtained from the ZVT. If the parameter is coded, a valid base register <u>must</u> be assigned <u>and</u> maintained throughout the module, since all Zeus macros that generate requests to subroutines do so via (internal) #CALL macros.

Note:

Only one DSECT of each type may be generated during any assembly. If more than one of a type is coded, its expansion will be bypassed and a message issued. Base register reassignment will be executed, however, if the 'BASE=...' parameter is coded.

#GETMEM

#GETMEM -- Allocate Main Memory

The #GETMEM macro is used to dynamically allocate main memory. Memory is allocated on a "first come, first served" basis for all contending tasks in the system. If memory is not immediately available, the requesting task can wait for it to become available. The address of the memory segment allocated is returned in register 1.

[label]	#GETMEM	{address} (r) char	[CQE=address] [,WAIT=address] [,ECB=address]

label

The address of the first executable instruction generated by the $\mbox{macro.}$

address (r) char

The amount of main memory requested, in bytes. Code one of the following:

- (1) The address of a word that contains the amount required.
- (2) A register enclosed in parentheses that contains the amount required.
- (3) A numeric character string equaling the amount required.

CQE=address

The address of the Core Queue Element associated with the request. If omitted, and memory is not immediately available, the request will not be queued.

WAIT=address

The address of the ECBLIST that contains the address of the ECB that will be posted when memory becomes available. If omitted,

no automatic wait is generated. It is possible for the task to wait at a later point so long as the integrity of the CQE is honored.

ECB=address

The address of the ECB to be posted when memory becomes available. If omitted, the address of the ECB is assumed to have been stored in bytes 8-12 of the CQE.

Registers Altered: 0, 1, 14, 15 External References: GETMEM Written by: Jean Garneau

¹Upon return from a #GETMEM without the 'WAIT' option, register 15 will equal zero if the memory requested was available. Register 1 will contain the address of the requested segment. If memory is not available, register $15 \neq z$ ero. If a CQE was available and memory was not available, the request was queued. When the memory becomes available, the ECB addressed by the CQE will be posted complete and the address of the memory segment will be stored in the rightmost three bytes of the ECB.

#GOTO -- Executive Conditional Branch

The #GOTO macro instruction is used to alter the instruction execution flow based on the evaluation of an expression.

[label]	#GOTO	address[,(expression)][,RET=register]

label

The address of the first executable instruction generated by the macro.

address

The address of the instruction to be branched to if the expression is evaluated to be true.

expression

The expression to be evaluated to determine if the branch will take place. The expression has one basic form as follows:

(operand A, operator, operand B)

Operands appear exactly as they would in standard assembler comparison instructions except for the following:

- (1) Decimal operation (i.e. CP) is not supported.
- (2) If the content of a register is to be evaluated the register must be enclosed in parentheses.
- (3) Literals are not indicated by a preceding equal (=) sign except when the literal is an 'A' type address constant (e.g., =A(X)).
- (4) A register may be evaluated against zero by coding a single 0 as the righthand operand.
- (5) Bits within a byte may be evaluated by coding one or more bit numbers separated by commas and enclosed within parentheses. Bits are numbered within a byte left to right 1 through 8.

operator

Code one of the following

EQ	equal
GE	greater than or equal
LE	less than or equal
LT	less than
GT	greater than
Bit-on	Equal if specified bit(s) on
Bit-off	Equal if specified bit(s) off
Bit-any	Equal if any bit(s) specified on

Examples

Expression	Is true if
(A, GT, B)	A greater than B.
(A(6), GE, B)	First 6 bytes of A greater than or equal to first 6 bytes of B.
(B(3), LT, C 'CAT')	First 3 bytes of B less than string 'CAT'
(5(10,7), EQ, 10C 'A')	Ten bytes addressed +5 from register 7 equal 'A's.
((5), EQ (4))	Register 5 equals register 4.
((5), LE, H '500') or ((5), LE, F '500')	Register 5 is less than or equal to 500.
((R4), eq, 0)	Register 4 is equal to zero.
(A, Bit-on, 2)	Bit 2 of byte addressed by A is on
(A+6, Bit-off, (1, 4, 5))	Bits 1, 4, and 5 of byte addressed by A+6 are off.
(O(R2), Bit-any, (1,2,3,4))	Any one or all of bits 1 through 4 as addressed by register 2 are on.

If the expression is omitted, the branch is made unconditionally.

RET=register


The register to be used as a return register in a 'BAL' instruction. If omitted, register 14 is assumed. A 'BAL' instruction is generated only if the expression is omitted <u>and</u> two or more addresses are coded. Addresses must be separated by commas with the entire list enclosed in parentheses. A single 'BAL' can be generated by coding the second address as an asterisk.

Examples:

#GOTO A #GOTO (A,*) #GOTO (A,*),RET=3 #GOTO (A,B,C)

unconditional branch to A
'BAL' to A, R14 = return register
'BAL' to A, R3 = return register
'BAL' to A, then B, then C,
R14 = return register

Registers Altered: See 'RET=' parameter.



2 OF AD AD 55023



#LDREG

#LDREG -- Load Register

The #LDREG macro provides a facility whereby other macros may decode parameter values and load appropriate registers with a minimum of effort. The #LDREG macro is intended to be used only within other macro descriptions.

#LDREG	(register[,option]),	(address)	[,'message']

register

the register from 0-15 which is to be loaded.

option

code one of the following or omit:

LA Load address

L Load full word

LH Load half word

LN Load address and complement

For effect of omission of 'option,' see following parameter definition.

{address} (r)

The value that is to be loaded into the register. If address is coded and option is omitted, 'LA' is assumed; if (r) is coded and option is omitted, 'LF' is assumed. If (r) is coded and 'LA' is the option, the effect in instruction executed is 'LA register.0(r).'

'message'

Code a message to be output (via a MNOTE statement) if the source data parameter is not available. If omitted, no message is generated.

Registers Altered: Any Written by: J. Garneau

#LOAD -- Load Transient Module

The #LOAD macro provides a facility whereby a task may request that a nonresident module be made available for use. If a copy of the module is currently available in main memory it will be used, otherwise the module will be loaded from an external storage device. The address of the module is returned in register 15. If register 15 equals 0, the module was not found or could not be loaded because of I/O problems.

[label]	#LOAD	EP={address	

label

The address of the first executable instruction generated by the macro.

EP={address}

The address of an 8-byte character string (padded with blanks if necessary) or a 1- to 8-byte character string enclosed in single quotes that identifies the module to be loaded.

LRB=address

The address of the Load Request Block used to process the #LOAD request. The LRB must be (at least) three words long.

WAIT=address

The address of the ECBLIST that contains the address of the ECB that will be posted complete when the loaded module is made available to the task.

If the WAIT keyword is omitted, no automatic wait is generated within the #LOAD macro. However, the task may issue a standard #WAIT at any later point so long as the integrity of the LRB is honored. In this case, upon return from the #LOAD, register 15 is negative if the request was successful (i.e., LRB was added to Load Request Queue), and zero if the request failed (i.e., module could not be located in library).

ECB=address

The address of the ECB to be posted complete when the module becomes available to this task. If omitted, and the WAIT keyword is coded, the ECB address is assumed to have been stored in bytes 8 through 12 of the LRB.

Registers Altered: 0, 1, 14, 15 External References: LDR0000 Written by: W. Underhill

#LPSW -- Load Program Status Word

The #LPSW macro will change the state of a program from supervisor to problem or from problem to supervisor, setting protect keys as required.

[label]	#LPSW	[state, KEY={address} (r)]
---------	-------	----------------------------

label

specifies the label of the first executable instruction generated by the macro.

state

code SUPV to load a supervisor state psw or PROB to load a problem state psw.

$$KEY = \begin{cases} address \\ (r) \end{cases}$$

The address of a byte in main storage, or a register, in which the protect key from the TCB can be stored after a change to Supervisor state or fetched from during the change to problem state.

Registers Altered: 0, 1, 14, 15, also see 'KEY=' parameter

External References: ZEUSSVC

#MOVE -- Move Data

The #MOVE macro allows data segments from 1 to 32,767 bytes to be moved, supports execution time length generation, and provides automatic EBCDIC to Hexadecimal conversion. Register 1, upon return from a #MOVE, will point to the last input character moved +1. CPU cycles and memory are optimized for each macro expansion.

[label]	#MOVE	[TO=address] [,FROM=address] $\left[TRNSLAT = \left\{ \frac{EBC}{HEX} \right\} \right]$]
---------	-------	--	---

T0=address

The address in main storage where the data will be moved. This address can take any format acceptable within the first operand of a 'MVC' instruction with the following additions:

(1) any length from 1 to 32,767 is valid

(2) the length may be loaded into a register and that register specified in the TO address length field, e.g. TO= 0((4),5)

If this parameter is omitted, register 1 is assumed to contain the address and register 14 the length.

FROM=address

The address in main storage from where the data are to be moved. This address can take any format acceptable within the second operand of a 'MVC' instruction. If omitted, register 0 is assumed to contain the from address.

TRNSLAT= $\left\{\frac{EBC}{HEX}\right\}$

If EBC is specified, or if the parameter is omitted, data are moved unmodified. If HEX is specified, each input data byte is converted to 2 output "HEX" bytes, that is, the actual number of input data bytes moved is one-half the number of characters specified as the move length.

Registers Altered: 0, 1, 14, 15

External References: MOVEOOO or MOVEO10

#OPENP

#OPENP -- Open Program/Subroutine and Initialize for Execution.

The #OPENP macro saves callers registers, assigns base registers, acquires and initializes program save areas.

[label] #OPENP [register] [,TYPE={REUS [,EXTEND=val-char][,TC	3=register]
--	-------------

label

Specifies the name to be assigned to the CSECT statement generated by the #OPENP macro. If omitted, the label 'MAIN' is assumed. The inclusion of any CSECT statement(s) prior to the #OPENP overrides the generation of the CSECT within the #OPENP.

register

Specifies the one or more registers (if more than one they must be separated by commas and the entire list enclosed in parentheses) that will become the program base registers. Registers are loaded and assigned, one by one, to contiguous 4095-byte segments of the program. If the parameter is omitted and the #OPENP is the first in the program, register 12 is assumed. If the parameter is omitted and the #OPENP is not the first in the program, no attempt to reassign a base register will be made; however all remaining parameters will be assembled normally.

TYPE= {REUS}

Specifies dynamic or static save area generation. If 'RENT' is coded, the save area will be acquired at execution time out of available storage within the partition or region assigned to the program. If 'REUS' is coded or the parameter is omitted, an inline save area will be generated. In either case, the address of the save area is loaded into register 13 and the save area is set to zeros (x'00').

EXTEND=val-char

Specifies the number of <u>words</u> that the save area will be extended. The address of the first byte of the first word of the extended

area is 72 (decimal) plus the contents of register 13. If this parameter is omitted, the standard OS 18-word save area is generated.

TCB=register

Code a register that contains the address of a Zeus TCB. If this parameter is selected and TYPE=RENT is coded, the save area that is acquired will be obtained via a #GETMEM Zeus macro (if memory is not available it will be waited for); if omitted, an OS GETMAIN will be executed.

External References: GETSAVE if TCB=r and TYPE=RENT are coded Written by: J. Garneau

#QFB -- Generate Queue Foundation Block

The #QFB macro provides a facility for describing and generating a queue foundation block.

[label] #QFB [QTYPE=(option,[...option])][,EXTEND=val-char]

label

The label of the first byte of the first word of the QFB generated within the macro.

QTYPE=option

Select one from each stack or as required:

(FIFO)

(NOTORDERED ORDERED[-ASCENDING]) ORDERED-DESCENDING

EXTEND=val-char

A numeric value from 1-4095 that defines the number of words the QFB should be extended. The extended area begins at offset 8 bytes from the first byte of the QFB. If omitted, the QFB is not extended.

#QUE -- Process Queue

The #QUE macro provides a facility whereby a routine may manipulate a queue. The queue must have been originally defined with a #QFB macro.

[label]	#QUE	ADD, ELEMENT = (address[, option]) DELETE
		[LOCATE (ID= {address} [,option])

label

The label of the first executable instruction generated by the macro.

ADD

add element to queue.

LOCATE

locate element and return its address in register 1. If element cannot be located, register 1 will equal 0 when control is returned.

DELETE

locate and delete specified element. If the element is deleted, register 1 will contain the address of the element; otherwise register 1 will equal 0.

The address of the element to be ADDed, DELETEd, or LOCATEd. If 0 is coded, either the absolute top or absolute bottom element on the queue will be affected (see option parameter).

ID={'char' } address}

The address of a 4-byte field (padded with blanks if necessary) or a 1- to 4-byte character string enclosed in single quotes which identifies the element to be deleted or located. The identifier is maintained in bytes 4-7 of the element and consists of any bit combination from X'00000000' to X'FFFFFFFF.'

option

As subparameter of ELEMENT parameter only:

Code TOP or BOTTOM to ADD/DELETE/LOCATE either the absolute top (first) or bottom (last) element on the queue (see "ELEMENT" parameter). If omitted, the request is processed as specified by the QFB options field.

As subparameter of ID parameter only:

Code TOP or BOTTOM to ADD/DELETE/LOCATE either the top (first) or bottom (last) element on the queue with the specified ID. Code LT (less than), GT (greater than), or GE (greater than or equal) to ADD/DELETE/LOCATE an element relative to some other element currently on the queue. If omitted, the request is processed as specified by the QFB options field.

QFB= {address} (r)

The address of the Queue Foundation Block associated with this queue. If omitted, register 0 is assumed to contain the QFB address.

Registers Altered: 0, 1, 14, 15 External References: QUEMGR Written by: Jean Garneau

#REGS

#REGS -- Register Symbol Generation

The #REGS macro provides automatic generation of register symbols.

#REGS [char][,PREFIX=char]

char

Code a number representing a register to be equated, or two numbers separated by commas and enclosed in parentheses representing a range of registers to be equated. If omitted, registers 0-15 will be equated.

PREFIX=char

Code one to six characters to specify the prefix to be assigned to each register selected. If omitted, the prefix "R" will be assumed. Checking to protect against generation of duplicate symbols will be performed only if the prefix "R" is either chosen or defaulted.

Written by: Jean Garneau

#SET -- Set Bit Status

The #SET macro instruction is used to alter the status of one or more bits within a byte.

[label]	#SET	byte-address,BIT-	ON OFF INV	},	(bit-char)
---------	------	-------------------	------------------	----	------------

byte-address

is the address in main storage of the byte that is to be altered.

BIT-

is the type of operation to be performed where:

ON - turns specified bit(s) on

OFF - turns specified bit(s) off
INV - Inverts status of specified bit(s)

bit-char

is a single bit number, or several bit numbers separated by commas and enclosed in parentheses. Bits are numbered within the byte, left to right, 1 to 8.

ALL

can be specified if all eight bits are to be affected. This parameter can be used in lieu of a specific request for each of the eight bits, for example, ALL instead of (1, 2, 3, 4, 5, 6, 7, 8).

Written by: J. Garneau

#STIMER

#STIMER -- Set Interval Timer

The #STIMER macro allows a task to set one or more interval timers. The task can wait for the specified interval to elapse or can continue processing. When the interval expires, the task can have either an ECB posted or can request that an exit routine be scheduled.

[label]	#STIMER	SEC=char[,TQE=address] [,WAIT=address	[,ECB=address]
---------	---------	---------------------------------------	----------------

label

The address of the first executable instruction generated by the macro.

SEC=char

Code a numeric character string with 0, 1, or 2 decimal places to specify the clock interval in seconds, tenths, and hundreds.

TQE=address

The address in main memory of the Timer Queue Element associated with this request. If omitted, register 1 is assumed to contain the TQE address.

WAIT=address

The address in main memory of an ECBLIST. The ECBLIST must contain the address of the ECB that will be posted when the interval expires. If omitted no automatic wait is generated by the macro. It is possible, however, for the task to wait at any later point so long as the integrity of the TQE is honored.

ECB=address

The address of the ECB to be posted complete when the interval expires. If omitted, the ECB address is assumed to have been stored in bytes 8 through 12 of the TQE with the sign bit off.

EXIT=address

The address of a routine to be executed when the interval expires. Upon entry to the Exit Routine, register 1 will point to the originating TQE. Words 4 to n of this TQE can be used to pass information to the exit routine. The exit routine is executed asynchronously with the task which requested the original interval. Any synchronization required between the requesting task and the exit task must be handled by the tasks themselves.

Registers Altered: 0, 1, 14, 15 External References: ITIMER Written by: J. Garneau

#TTIMER

#TTIMER -- Test Zeus Interval Timer

The #TTIMER macro is used to test, cancel or force completion of an interval timer previously set by a #STIMER macro.

[label]	#TTIMER	[type][,TQE=address]
	# =	[0, 1 0, 1 0, 1 0, 1 0, 1 0, 1 0, 1 0,

label

specifies the address of the first executable instruction generated by the macro.

type

code one of the following:

REMAINING Return time remaining this interval (in hundreds of

seconds) in the second word of the specified TQE.

This is default type if parameter omitted.

COMPLETE Force ECB referenced by specified TQE to be posted

complete and cause TQE to be removed from timer

queue.

CANCEL Cause TQE to be removed from timer queue (ECB not

posted).

TQE=address

The address in main memory of the TQE (Timer Queue Element) associated with the request. If omitted, register 1 is assumed to contain the TQE address.

Registers Altered: 0, 1, 14, 15 External References: ITIMER Written by: J. Garneau

#WAIT

#WAIT -- Wait for Event Completion

The #WAIT macro instruction allows a task to wait for the completion of one or more events. The event may be resource availability, I/O, timer interval completion, memory availability, task synchronization, and so forth. Upon return from a #WAIT register O contains the address of the ECB posted complete and register 15 contains its offset in the LIST (i.e., ECB=1, R15=0; ECB=3, R15=8).

[label]	#WAIT	[{ecblist-address ECBLIST=ecblist-address}]	[,EPADDR=entry-address]
---------	-------	---	-------------------------

label

specifies the address of the first executable instruction generated by the macro.

{ecblist-address {ECBLIST=ecblist-address}

specifies the address in main memory of the ecblist that contains the addresses of one or more ECB's to be waited on. Each ECB address is 4 bytes in length. The last ECB address must have bit 0 (i.e. X'80') on. If omitted, register 1 is assumed to contain the ecblist address.

EPADDR=entry-address

The address in main memory of a word which contains the Dispatcher address. If the Dispatcher address has previously been loaded into a register, this parameter may be coded (r) where r is the register so loaded. If the parameter is omitted, a V-type address constant for the entry point of the Dispatcher.

Registers Altered: 0, 1, 14, 15 External References: DSPTCHR Written by: J. Garneau

#ZEUSSVC

#ZEUSSVC -- Execute Zeus SVC

The #ZEUSSVC macro executes an SVC instruction which is stored in a "remote" CSECT. (The purpose of this is to allow the Zeus SVC to be changed with a single assembly and a relink-edit of Zeus.) Upon return, register 15 will contain the address of the Zeus incore address table and register 0 the address of the partition or region TCB.

[label] #ZEUSSVC

label

specifies the address of the first executable instruction generated by the macro.

Registers Altered: 0, 1, 5 External References: ZEUSSVC Written by: J. Garneau

Chapter 3

SYSTEM DATA AREAS

The operation of Zeus requires that certain control blocks and queue elements be created and maintained. Table 2 contains a list of these areas, a brief description of each, and their primary use.

Table 2

Control Blocks

Name		Used For	Number Required	
LCB:	Line Control Block	Control I/O activity on a TP Line or local channel	1 per device type per line	
TQE:	Timer Queue Element	Support a Zeus interval timer	unlimited	
CQE:	Core Queue Element	Support conditioned memory request	unlimited	
TCB:	Terminal Control Block	Control I/O activity on a terminal device	1 per device	
ZVT:	Zeus Vector Table	Cross reference address table for main Zeus components	1 per Zeus	
QFB:	Queue Foundation Block	Anchor for each queue	unlimited	
LRB:	Load Request Block	Support transient module load function	unlimited	

A description of each Control Block and Queue Element is presented in this Chapter, organized alphabetically within two sections—Section 1, Control Blocks and Tables and Section 2, Queue Elements.

SECTION 1: CONTROL BLOCKS AND TABLES

Descriptions of the Zeus Line Control Block (LCB), Queue Foundation Block (QFB), Terminal Control Block (TCB), and Vector Table (ZVT) are provided in this section. For each, an overview is presented first, followed by a detailed description.

LINE CONTROL BLOCK

The Line Control Block (LCB) is used by the Line Task to control I/O on a remote or local communication channel. More than one LCB may be assigned to a given channel. However, I/O on LCBs assigned to separate channels is asynchronous while I/O on LCBs assigned to the same channel is synchronous.

Synchronization of multiple LCBs on a single channel is accomplished by assigning the channel exclusively to each LCB in turn. The #ENQ/#DEQ Zeus macros are used for this purpose.

Line Control Block-Overview

05000500		
	DEC	SDECB
DECTYPE	last op. DEC	LNGTH
DECONLTT		DECDCBAD
DECAREA		
DECSENS0	DECSENS1	DECCOUNT
DECCMCOD		DECENTRY
DECFLAGS	DECRLN	DECRESP
DECTPCOD	DECERRST	DECCSWST
	DEC	ADRPT
	DEC	POLPT
LDECBA	19	
LTCBC	1	LTCBA
	-	
LPOLS	<u> </u>	LLISTA
LP	OLLC	LADDRC
LCBFLGS		LCBNEXT
ι	TQE	LCQE
		LTH

	Line Con		ailed Description	
	Offset	Bytes and Alignment	Field Name	Field Description, Contents, Meaning
	0(0)	0	DECB	
П	0(0)	4	DECSDECB	Event control block
П	4(4)	1	DECTYPE	Type field
	5(5)	. 1		Last operation
n	6(6)	2	DECLNGTH	Length
П	8(8)	1	DECONLTT	Reserved for on-line test
	8(8)	4	DECDCBAD	DCB address
П	12(C)	4	DECAREA	Area address
L	16(10)	1	DECSENS0	First sense byte
	17(11)	. 1	DECSENS1	Second sense byte
	18(12)	2	DECCOUNT	Residual count
L	20(14)	1	DECCMCOD	Command code
	20(14)	4	DECENTRY	Terminal list address
	24(18)	1	DECFLAGS	Status flags
	25(19)	. 1	DECRLN	Relative line number
	26(1A)	2	DECRESPN	Response field
	28(1C)	1	DECTPCOD	TP op code
L	29(1D)	. 1	DECERRST	Error status
	30(1E)	2	DECCSWST	CSW status
	32(20)	4	DECADRPT	Address of current addressing entry
L	36(24)	4	DECPOLPT	Address of current polling entry
0	40(28)	1	LDECBA	Reserved for DSPTCHR
	41(29)	. 3		DECB address
	44(2C)	1.	LTCBC	Count of this line's TCBs
П	44(2C)	4	LTCBA	Address of first TCB on this line's queue
	48(30)	1	LPOLS	Polling list control byte save area
	48(30)	4	LLISTA	Line polling list address
П	52(34)	2	LPOLLC	Number of active entries in polling list
	54(36)	2	LADDRC	Number of writes pending
	56(38)	1	LCBFLGS	
			1	Busy
L			. 1	Poll
			1	Interval
			1	Write
			1	Memory wait
	56(38)	4	LCB NEXT	Address of next LCB on queue
	60(3C)	12	LTQE	Line timer queue element
U	60(3C)	12	LCQE	Line core queue element
	72(48)	4	LLTH	LCB length

QUEUE FOUNDATION BLOCK

The head pointer to each queue is located in a Queue Foundation Block. The Queue Foundation Block is used as an anchor for all Zeus Queues. For example, the timer queue, the memory queue, and the load request queue are all anchored with their own QFBs.

Queue Foundation Block-Overview

Offset		Word
0(0)	STATUS	First element address
4(4)	ТҮРЕ	Last element address
8(8)	Op	otional Extended Area

Queue Foundation Block-Detailed Description

Offset	Bytes and Alignment	Field Name	Field Description, Contents, Meaning
0(0)	1	1	Status bytes - null queue
1(1)	. 3		Address of first element in queue
4(4)	1	TYPE	
		.1	Ascending queue
		1	Descending queue
		1	Last in/first out - LIFO
		1	First in/first out - FIFO
		1	Count
		X XX	Reserved
5(5)	. 3		Address of last element in queue
8(8)	Any	Data	Optional extended data area

ZEUS TERMINAL CONTROL BLOCK

The Terminal Control Block (TCB) is used by the Terminal Task to control I/O on a (terminal) device.


Zeus Terminal Control Block-Overview

TCBIDENT	TCBCOUNT
TCBECB	
TPIOECB	
BUFSIZE	
LINEREM	
POSREM	
RBLOKAD	R
RELBLOCI	<
TCBRJE	
SBUF1L	
SBUF2L	
REQDCB	
ACHAINSA	1
SBUF1A	
SBUF2A	
PAGELINE	
PAGEND	

unused	
ALCB	
ATAENTR'	
ARODECB	

(Continued)

Zeus Terminal Control Block-Overview (Continued)



Zeus Terminal Control Block-Detailed Description

Offset	Bytes and Alignment	Field Name	Field Description, Contents, Meaning
0(0)	3	TCBIDENT X'E3C3C2'	Characters 'TCB' to identify control block
3(3)	1	TCBCOUNT	TCB's number
4(4)	4	TCBECB	ECB for CPU synchronization
8(8)	4	TPIOECB	ECB for terminal I/O
12(C)	4	BUFSIZE F'1048'	Buffer size for terminal READ operation
16(10)	4	LINEREM	Unused lines remaining in terminal output buffer
20(14)	4	POSREM	Unused characters remaining in terminal output buffer
24(18)	4	RBLOKADR	Address in page where miscellaneous system messages are to be stored
28(1C)	4	RELBLOCK	Relative block number of text to be retrieved from or stored on direct access storage device
32(20)	4	TCBRJE	Used by RJE subsystem
36(24)	4	SBUF1L	Length of buffer one
40(28)	4	SUBF2L	Length of buffer two
44(2C)	4	REQDCB	Address of DCB associated with current request for text storage or retrieval this TCB
48(30)	4	ACHAINSA	Address of initial save area in chain currently attached to this TCB
52(34)	4	SBUF1A	Address of buffer one
56(38)	4	SBUF2A	Address of buffer two
60(3C)	4	PAGELINE	Next available position in terminal output buffer
64(40)	4	PAGEND	Last position in terminal output buffer
68(44)	4		unused
72(48)	4	ALCB	Address of Zeus Line Control Block
76(4C)	4	ATAENTRY	Address of terminal addressing entry
80(50)	4	ARQDECB	Address of requestor DECB for this terminal
84(54)	4	ARQIOA	Address of requestor I/O area
88(58)	4		unused
92(5C)	4	TCBNEXT	Address of next TCB
96(60)	4	TPIOECBL	
	1	1	
	. 3		Address (list) of ECB for terminal I/O
100(64)	4	TCBECBL	
	1	1	Address (list) of CPU synchronization ECB (TCB)
104(68)	. 3	NTPDECBL	Address (list) of GPO synchronization EGB (TCB)
104(00)	1	1	
	. 3		Address (list) of non-IP DECB for I/O

(Continued)

Zeus Terminal Control Block-Detailed Description (Continued)

Offset	Alignment	Field Name	Field Description, Contents, Meaning
108(6C)	4	DECBDA	Event control block
	1	1	Type field
	. 1	. 1 1	Type field
	2		Length
	4		DCB address
	4		Area address
	4		IOB address
	4		Key address
	4		Block reference address
140(88)	1	GLOSBLK	Relative position on terminal for glossary 'ROLL' request
	. 3		unused
	2		unused
146(8E)	1	PAGECB	Page control byte
		1	Page contains valid data
		. 1	Prefix processing completed
		1	Suffix processing completed
		1	Processing complete
		1	CUR requested
		1	ROL requested
		1 .	DEL requested
		1	MOD requested
147(8F)	1	PAGECB2	Page control byte extension
		1	COP requested
		. 1	CRE requested
		1	DIS requested
		1	RES requested
		1	LIS requested
		1	LOC requested
		1 .	cursor reset required
		1	commands will be executed
148(90)	8	USERNME	User name
156(98)	2	USERID	User identification
158(9A)	2		unused
160(9C)	2		unused
162(9E)	1	CMID	C'(' command id
163(9F)	1	0100 0000	space
164(A0)	4	AQWORK	Address of work space currently available
168(A4)	1	LSTAT	Line status byte
100(/11/		1	TCB processing READ request
		. 1	TCB processing WRITE request
		X	reserved
		1	TCB waiting for terminal output
		1	TCB waiting for terminal input
		X	reserved
		1.	Terminal logged on
		1	RJE function in process

Zeus Terminal Control Block-Detailed Description (Continued)

Offset	Bytes and Alignment	Field Name	Field Description, Contents, Meaning
169(A5)	. 1	INFOBLK	Relative position on terminal of the 'INFO' input area
170(A6)	1	MSGBLK	Relative position on terminal for system message presentation
171(A7)	1	FILECB 1 .XXXXXXX	File control byte Locate record with key reserved
172(A8)	4	AIOBUF	Address of terminal I/O buffer
176(AC)	12	TCQE	TCB core queue element (CQE)
176(AC)	12	TTQE	TCB time queue element (TQE)
188(B8)	2	CURCORD	XY cursor co-ordinates
190(BA)	2	DATACORD	XY data co-ordinates
192 (BC)	4	TCBL	Length of TCB

ZEUS VECTOR TABLE

The Zeus Vector Table (ZVT) is used by all system routines to acquire data and addresses of system resources.

Zeus Vector Table-Overview

Offset -	Word
0(0)	ZDSPTCHR
4(4)	ZMASTER
8(8)	ZITIMER
2(C)	ZRJE0100
6(10)	TCBQ
20(14)	ZLCBQ
24(18)	ZCOREQ
28(1C)	ZTIMERQ
32(20)	ZCNVTOOO
36(24)	ATE
10(28)	ETA

(Continued)

Zeus Vector Table-Overview (Continued)

Offset -	Word
44(2C)	
48(30)	TPDCB
	ZNTPDCBT
52(34)	ZWTR00
56(38)	ZLINE10
60(3C)	
64(40)	ZTERMIO
68(44)	LTE
	ETL
72(48)	ZCTLTAB
76(4C)	ZMOVE
80(50)	ZMSCHD
84(54)	
88(58)	ZCHTB
92(5C)	ZCTB
96(60)	ZCMNDPC1
	ZCMNDPC2
100(64)	ZGETSAVE
104(68)	ZGETCORE
108(6C)	
112(70)	ZFREECOR
116(74) 120(78)	
124(7C)	ZQUEMGR
	ZRCVRMGT
128(80)	ZRESET
132(84)	ZRTERM
136(88)	
140(8C)	ZSCAN
	ZSTACK

Zeus Vector Table—Overview (Continued)

Offset	→ Word — →
144(90)	ZSTATUS
148(94)	ZPOOLA
152(98)	ZLDR0100
156(9C)	ZLDR0000
160(A0)	
164(A4)	ZENQCTRL
168(A8)	
172(AC)	ZCNTXCTL
176(B0)	ZMOVEX
	ZRITQE
180(B4)	ZGCOUNT
184(B8)	ZLDR0200
188(BC)	ZSUPV
192(C0)	ZPROB
196(C4)	ZMOVE000
200(C8)	ZMOVE010
204(CC)	ZWTERM
208(D0)	ZCRTREAD
212(D4)	ZNTPIO
216(D8)	
220(DC)	ZEMPTY
224(EO)	ZFULL
228(E4)	ZZS0B001
	ZVTL

Zeus Vector Table-Detailed Description

Offset	Bytes and Alignment	Field Name	Field Description, Contents, Meaning
0(0)	4	ZDSPTCHR	Address of dispatch subroutine
4(4)	4	ZMASTER	Address of ZEUS command interface
8(8)	4	ZITIMER	Address of interval timer task
12(C)	4	RJE0100	Address of reader/interpreter task
16(10)	4	TCBQ	Address of first TCB on queue
20(14)	4	ZLCBQ	Address of first LCB on queue
24(18)	4	ZCOREQ	Address of first CQE on queue
28(1C)	4	ZTIMERQ	Address of first TQE on queue
32(20)	4		unused
36(24)	4	ATE	Address of ASC11 to EBCDIC translate table
40(28)	4	ETA	Address of EBCDIC to ASC11 translate table
44(2C)	4	TPDCB	Address of TP DCB
48(30)	4	ZNTPDCBT	Address of non-TP DCB table
52(34)	4	ZWTR00	Address of writer task
56(38)	4	ZLINEIO	Address of line I/O task
60(3C)	4	ZTERMIO	Address of terminal I/O task
64(40)	4	LTE	Address of line code to EBCDIC translate table
68(44)	4	ETL	Address of EBCDIC to line code translate table
72(48)	4	ZCTLTAB	Address of ASC11 control character table
76(4C)	4	ZMOVE	Address of move subroutine
80(50)	4	ZMSCHD	Address of master schedule subroutine
84(54)	4	ZCHTB	Address of convert hex to binary subroutine
88(58)	4	ZCTB	Address of convert to binary subroutine
92(5C)	4	ZCMNDPCI	Address of command processing subroutine-part 1
96(60)	4	ZCMNDPC2	Address of command processing subroutine-part 2
100(64)	4	ZGETSAVE	Address of GETSAVE subroutine
104(68)	4	ZGETCORE	Address of GETCORE subroutine
108(6C)	4	ZFREECOR	Address of FREECORE subroutine
112(70)	8		unused
120(78)	4	ZQUEMGR	Address of QUEMGR subroutine
124(7C)	4	ZRCVRMGT	Address of recovery management task
128(80)	4	ZRESET	Address of output buffer allocation subroutine
132(84)	4	ZRTERM	Address of terminal I/O interface subroutine
136(88)	4	ZSCAN	Address of SCAN subroutine
140(8C)	4	ZSTACK	Address of STACK subroutine
144(90)	4 .	ZSTATUS	Address of STATUS subroutine
148(94)	4	ZPOOLA	
	1	1	No subpool
	. 3		Address of Zeus subpool

- (Continued) -

Zeus Vector Table-Detailed Description (Continued)

Offset	Bytes and Alignment	Field Name	Field Description, Contents, Meaning
152(98)	4	ZLDR0100	Address of transient routine loader task
156(9C)	4	ZLDR0000	Address of transient routine queue manager
160(A0)	4	ZENQCTRL	Address of ENQ/DEQ processor
164(A4)	4		reserved
168(A8)	4	ZCNTXCTL	Count subroutine 'XCTL' control
172(AC)	4	ZMOVEX	Address of character to hex move subroutine
176(B0)	4	ZRITQE	Address of reader-interpreter QFB
180(B4)	4	ZGCOUNT	Address of routine to format and dump
184(B8)	4	ZLDR0200	Address of transient table dump routine
188(BC)	4	ZSUPV	Address of supervisor state routine
192(C0)	4	ZPROB	Address of problem state routine
196(C4)	4	ZMOVE000	Address of move routine
200(C8)	4	ZMOVE010	Address of movex routine
204(CC)	4	ZWTERM	Address of TP output interface routine
208(D0)	4	ZCRTREAD	Address of real terminal routine
212(D4)	4	ZNTPIO	Address of non-TP I/O routine
216(D8)	4	ZEMPTY	Address of TP output buffer empty routine
220(DC)	4	ZFULL	Address of TP output buffer full routine
224(E0)	4	INITO	Address of ZEUS first level initialization routine
228(E4)	2	ZVTL	Length of ZVT

SECTION 2: QUEUE ELEMENTS

Descriptions of the Zeus Core Queue Element (CQE), Load Request Element (LRE), Resource Queue Element (RQE), and Timer Queue Element (TQE) are presented in this section.

CORE QUEUE ELEMENT

The Core Queue Element (CQE) is used, in conjunction with a conditional memory request, to queue a request for more main memory than is currently available.

Core Queue Element-Overview

Status	Link
Reserved	Size of Request

Core Queue Element-Detailed Description

Offset	Bytes and Alignment	Field Name	Field Description, Contents, Meaning
0(0)	1 . 3	Status 1	Last entry on Queue Reserved Address of next CQE on core request queue.
	. •	Link	If last CQE on queue link will address previous CQE.
4(4)	1 . 3	XXXXXXXX size	Reserved Amount of memory required to satisfy this request.
8(8)	4	Pose	Address of ECB which is to be posted complete when enough core becomes available to satisfy the request. When the ECB is posted complete the address of the core element obtained will be stored in its rightmost three bytes. The CQE is then removed from the Core Queue.

LOAD REQUEST ELEMENT

The Load Request Element (LRE) is used to process a load request for a transient module that is not currently in main memory.

Load Request Element-Overview

Status	Link	
Table Entry address		
	ECB address	

Load Request Element-Detailed Description


Offset	Bytes and Alignment	Field Name	Field Description, Content, Meaning
0(0)	1	Status	Last Entry on Queue
		.xxx xxxx	Reserved
	. 3	Link	Address of next LRE: on Load Request Queue. If last LRQ on queue link will address previous CQE
4(4)	4	Table	Address of table entry for module to be loaded
4(4)	4	Post	Address of ECB to be posted when module becomes available

The state of the second second

RESOURCE QUEUE ELEMENT

The Resource Queue Element is used to synchronize accessing of system resources.

Resource Queue Element-Overview




Resource Queue Element-Detailed Description

Offset	Bytes and Alignment	Field Name	Field Description, Content, Meaning
0(0)	1	Status 1	Last Entry on Queue
	. 3	.XXX XXXX Link	Reserved Address of next RQE on Resource Queue If last entry on queue, link points to previous entry
4(4)	4	RName	Resource nameany four characters, X'00' thru X'FF', may be used. If the name is less than 4 characters, it must be kept adjusted and padded with blanks
8(8)	4	Post	Address of Event Control Block

TIMER QUEUE ELEMENT

The Timer Queue Element (TQE) is used to create and maintain an interval timer.

Timer Queue Element—Overview



Timer Queue Element—Detailed Description

Offset	Bytes and Alignment	Field Name	Field Description, Content, Meaning
0(0)	1	Status	
		1	Last Entry on Queue
		.XXX XXXX	Reserved
	. 3	Link	Address of next TQE on Timer Queue. If last element on the Timer Queue address of previous TQE.
4(4)	4	Time	Remaining interval this element at time of last Timer Queue 'post'. If this TQE is the first on the queue, then this interval was used to set the last 'real' clock.
8(8)	1	Post	
		1	Exit address in next 3 bytes
		0	ECB address in next 3 bytes
		XXXXXXX	Reserved bits
8(8)	1 3		When the TQE interval is reduced to zero, the TQE is removed from the queue. Depending upon FLGS either routine is scheduled. This field contains either the exit address or the ECB pointer.

Chapter 4

UTILITY PROGRAMS

This chapter describes the programs necessary to implement, operate and maintain the Zeus system. A summary of the programs contained in this chapter is presented below.

Program Name	Function
BLDIFLE1	Format key file
BLDIFLE2	Add records to key file
BLDIFLE3	Replace records in key file
BLDXFILE	Format text files
BLDTFILE	Add modules to transient routines file
BLDRFILE	Format Remote Job Entry file
IMACOPY	Copy one or more files
IMAPDSMD	Update a partitioned data set
IMAPTPCH	Print/punch utility

BLDIFLE1

FUNCTION:

To format a direct access file for input of the glossary

records

INPUT:

None

OUTPUT:

A disk file of 1200 dummy records formatted for 40-byte

keys

PROCESS:

The output file is opened.

1200 dummy records are written.

The file is closed.

MACROS USED:

#REGS, #OPENP, #CLOSEP

ROUTINES

CALLED:

None

SIZE IN

BYTES:

434 bytes

EXTERNAL

REFERENCES:

None

EXIT:

To address in R14

WRITTEN BY:

BLDIFLE2

FUNCTION:

To add records to the glossary (IFILE)

INPUT:

A card file containing the QFILE record numbers of the

records to be transferred to the IFILE;

The QFILE

OUTPUT:

A printed listing of keys and relative record numbers of records added to the IFILE. Both the derived and

actual record numbers are listed.

A disk file organized with 40-byte keys and 800-byte

data records.

A punched or printed error file containing error messages

and images of the input card records that caused the

errors.

PROCESS:

The input card file is read to determine which QFILE record is to be added to the IFILE. The QFILE record is read. The first line of the record, up to the delimiting period, carriage return characters, or the first 40 bytes is used as input to SCANKEY which removes spaces and special characters to and from the key and derives an IFILE relative record number for the record to be added. The record and key are written in the IFILE. The printed listing giving key and actual and derived relative locations is written. Any errors cause an error message to be written along with

the card record that caused the error.

MACROS

USED:

#OPENP, #REGS, #CLOSEP

ROUTINES

CALLED:

SCANKEY, CTB

SIZE IN BYTES: 3,294 bytes

EXTERNAL

REFERENCES:

SCANKEY, CTB

EXIT:

To address in R14

WRITTEN BY:

BLDIFLE3

FUNCTION:

To update the IFILE.

INPUT:

A card file containing relative record numbers of QFILE records to be transferred to the IFILE.

The OFILE.
The IFILE.

OUTPUT:

The updated IFILE.

A printed listing of IFILE records added or replaced.

A printed or punched error file.

PROCESS:

The files are opened. The card file is read to obtain the relative record number of the QFILE record that is to be transferred. The first 40 bytes or the characters up to the delimiter, period-carriage return, of the QFILE records are used as input to SCANKEY, which removes space and special characters to form the record key and derives a relative record number for the IFILE record.

The IFILE is read. If no record with the key being used is found, the QFILE record is written in the IFILE. If a record is found in the IFILE, with the key being used in the search, this record is checked to determine if it is "active." If so, an error message is written. If not, the QFILE record is written in place of the inactive IFILE record. A printed listing is written giving the keys and actual and derived relative record number of all records written in the IFILE.

An error file is produced for records that could not be written. A record may not be written because it was to replace an "active" record or because there was no room within the specified search limits.

MACROS USED:

#OPENP, #REGS, #CLOSEP

ROUTINES

CALLED:

SCANKEY

SIZE IN

BYTES:

3,718 bytes

EXTERNAL

REFERENCES:

SCANKEY

EXIT:

To address in R14

WRITTEN BY:

BLDXFILE

FUNCTION:

To allocate space for the D, F, and Q files.

INPUT:

R1 PARM field

OUTPUT:

A direct access file containing the number of records specified in the PARM field and of the size specified in the DCB BLKSIZE field on the DD card; a print file

containing error messages.

PROCESS:

The files are opened. The parm field is examined to see if the number of records has been specified. If not, an error message is printed and processing stops. If a number of records exceeding the maximum 32-bit binary number (2,147,483,647) is specified, an error message is pointed and processing stops. If a valid number of records is specified, this number of records is written. The records are formatted with the first 100 bytes set to zero and the remainder--up to 1,028 bytes--set to spaces. If errors occur while writing a record, an error message is printed and processing continues. When the last record is written, the files are closed and processing ceases.

MACROS

USED:

#REGS, #OPENP, #CLOSEP

ROUTINES

CALLED:

None

SIZE IN

BYTES:

1,964 bytes

EXTERNAL

REFERENCES:

None

EXIT:

To address in R14

WRITTEN BY:

BLDTFILE

FUNCTION:

To load Zeus transient routines in executable form into partitioned data set.

INPUT:

R1 Parm field for name of load module Linkage Editor output (SYSLMOD).

OUTPUT:

The specified transient routine loaded into IMP1.TFILE.

PROCESS:

The parm field is checked. If no name has been specified, or if a name exceeding eight characters is specified, an appropriate error message is printed and processing is discontinued. If a name with a valid length is specified, it is saved. The files are opened (if either file fails to open, an error message is printed and processing is discontinued). A BLDL instruction is issued for the input data set. The results are checked to make sure that the module in question does exist in executable form.

If not, the appropriate error message is printed and processing is discontinued. If so, the size is checked. If the size is eight bytes or 7,000 bytes, an error message is printed and processing discontinues. If the size is valid, the module is loaded and written into IMP1.TLOAD.

The PDS directory is updated to reflect the addition of the member with a STOW instruction. If an error occurs, the appropriate message is printed and processing discontinues. If there is no error the files are closed, a message indicating that the module has been successfully placed in the PDS is printed and processing discontinues.

ZEUS MACROS

USED:

#CLOSEP, #OPENP, #GOTO, #REGS

ROUTINES

CALLED:

None

SIZE IN BYTES: 1,330 bytes

EXTERNAL

REFERENCES: None

EXIT:

To address in R14

WRITTEN BY:

W. Underhill

BLDRFILE

FUNCTION:

To build the RFILE

INPUT:

Parm field data to specify file size

OUTPUT:

RFILE containing the specified number of 1,124-byte records. Records 0 and 1 are special records for use

by the RJE functions of Zeus.

PROCESS:

The parm field is checked. If it is missing an error message is printed and processing ceases. If the file size is <8 or if (file size -8)/8 is >1,020 an error message is printed and processing ceases. If a valid file size is specified, records 0 and 1 are formatted and written. The remainder of the file is written with records formatted with zeroes. A message is printed, upon completion, saying that the file has been formatted and giving the record number of the last record. Processing ceases.

ZEUS MACROS

USED:

N/A--program written in PL/1

ROUTINES

CALLED:

WTP

SIZE IN

BYTES:

1,048 bytes

EXTERNAL

REFERENCES:

WTP

EXIT:

To System

WRITTEN BY:

W. Underhill

IMACOPY

FUNCTION:

To copy any data set

INPUT:

Data set(s) to be copied--up to 10

OUTPUT:

Copied data set(s)

PROCESS:

The input data set is copied to the output data set. The process is repeated for each input and output data

set specified.

ZEUS MACROS

USED:

#OPENP, **#CLOSEP**

ROUTINES

CALLED:

None

SIZE IN

BYTES:

946 bytes

EXTERNAL

REFERENCES:

IMACOPY

EXIT:

To address in R14

WRITTEN BY:

Jean A. Garneau

NAME: IMAPDSMD

FUNCTION: To add/replace/delete members of a partitioned data set

(PDS).

INPUT: Parameter card indicating what operation is to be per-

formed; member to be added or replaced.

OUTPUT: Modified PDS.

PROCESS: The parameter card is read and interpreted to determine

what operation is to be performed; the name of the member; whether to print the entire input data; whether an identification is to start in location 73 and if so what it is; and what the increment for sequencing is to

be. The specified PDS is then modified as indicated.

ZEUS MACROS

USED: #REGS, #OPENP, BSECT, RET, CLOSEP

ROUTINES

CALLED: None

SIZE IN

BYTES: 3,937 bytes

EXTERNAL REFERENCES: None

EXIT: To address in R14

WRITTEN BY: Jean A. Garneau

NAME: IMAPTPCH

FUNCTION: Utility for printing or punching sequential data sets.

INPUT: Sequential data set. PARM field indicating operation to

be performed.

OUTPUT: Printed or punched data set.

PROCESS: The PARM field is interrogated to determine which opera-

tion is to be performed; at which record in the data set the operation is to begin; whether any subsequent records are to be skipped; whether the entire operation is to be repeated, and if so for how many times; whether sequence numbers are to be placed in the output record (if punched) and if so, what the initial value and the increment are to be; whether printed output is to be spaced, and if so how many blank lines (0 to 3) are to be between records; whether conversion to hexadecimal or to EBCDIC is to be made. The specified operations are performed and the

output data set written.

ZEUS MACROS

USED: #REGS, #OPENP, #GOTO, #BITS, #BSECT, #RET, #CLOSEP

ROUTINES

CALLED: CTB, MOVEX, MOVE

SIZE IN

BYTES: 3,176 bytes

EXTERNAL

REFERENCES: CTB, MOVEX, MOVE, IECTTRNS, IMAPTPCH

EXIT: Address in R14

WRITTEN BY: Jean A. Garneau

Chapter 5

PROCEDURES

This chapter lists all the Job Control Language (JCL) procedures required to support the Zeus system. A summary of the procedures, along with a brief description of them, is presented in the following list:

Member Name	Description
#ASMFC	Assemble and store object module in Zeus library
# ASMFCG	Assemble and Go
#ASMFCL	Assemble and Linkedit
#ASMFCZ	Assemble and store object code in Zeus object code file
# ASMFCLG	Assemble, link, and go
#ASMFCLT	Assemble, linkedit, and store executable module in Zeus Transient Routine file
MOVE	Mode data set
COMPRESS	Compress a partitioned data set
PDSMOD	Modify a partitioned data set
RDRZ	Zeus reader
RGET	Extract data set off-line from RJE file
RPUT	Add data set off-line to RJE file
UT	Print/Punch file
ZEUS	Zeus procedure
ZOLD	Zeus Job (Old Zeus)
ZREG	Zeus Job (Regular Zeus)
ZTEST	Zeus Job (New Zeus)

```
MEMBER NAME #ASMFC
         PROC
               NAME=TEMP
//ASM
         EXEC ..
               PGM=IEUASM, PARM="NODECK, LOAD, NOXREF", TIME=20
//SYSLIB DD
                DSN=IMP1.ZMACRO.DISP=SHR
                DSN=SYS1.MACL IB, DISP=SHR
11
         DD
//SYSPRINT DD
               SYSOUT=A,DCB=(LRECL=121,RECFM=FBM,BLKS[ZE=363,BUFNO=5)
               SPACE=(CYL, (3,3)), UNIT=(SYSDA, SEP=SYSPRINT)
//SYSUT1 DD
                SPACE=(CYL, (3,3)), UNIT=(SYSDA, SEP=(SYSPRINT, SYSUT1))
//SYSUT2 DD
//SYSUT3 DD
               SPACE=(CYL, (3,3)),UNIT=(SYSDA,
                SEP=(SYSUT2,SYSUT1,SYSLIB))
11
//SYSGO DD
                DISP=OLD.DSN=SYS1.GARN(&NAME)
```

```
MEMBER NAME #ASMFCG
//ASM EXEC PGM=IEUASM,PARM="NODECK,LOAD",TIME=10
//SYSPRINT DD SYSOUT=A.DCB=(LRECL=121,RECFM=FBM.BLKSIZE=363,BUFNO=9)
//SYSLIB DD
               DSNA ME=IMP1.ZMACRO, DISP=SHR
         00
               DSNAME=SYS1.MACLIB, DISP=SHR
//SYSUT1 DD SPACE=(CYL,(3,3)),UNIT=(SYSDA,SEP=SYSPRINT)
//SYSUT2 DD SPACE=(CYL,(3,3)),UNIT=(SYSDA,SEP=(SYSPRINT,SYSUT1))
//SYSUT3 DD
               UNIT=(SYSDA,SEP=(SYSUT2,SYSUT1,SYSLIB)),
11
               SPACE=(CYL,(3,4))
//SYSGO DD
               UNIT=SYSDA, DSNAME=&LOADSET, SPACE=(CYL,(1,1)),DISP=(MOD,
11
               PASS)
//GO
         EXEC
               PGM=LOADER, COND=(8, LT, ASM)
//SYSLIB DO
               DSNAME=HUM1.SUBRTLIB,DISP=SHR
         DD
               DSN=IMP1.SUBRTLIB,DISP=SHR
//SYSLIN DD
               CSNAME= * . ASM. SYSGO, DISP= (OLD, PASS)
               DONAME = SYSDIN
         DO
11
//SYSLOUT OD
               SYSOUT =A
//SYSPRINT UD
               SYSOUT = A
//SYSUDUMP DD SYSOUT=A
```

```
MEMBER NAME #ASMFCL
         EXEC PGM=IEUASM, PARM='LOAD, NODECK', TIME=10
//ASM
//SYSPRINT DD .SYSOUT=A, DCB=(LRECL=121, RECFM=FBM, BLKSIZE=363, BUFNO=9)
//SYSLIB DD
               DSNA ME=IMP1.ZMACRO, DISP=SHR
11
         DD
               DSNAME=SYS1.MACLIB.DISP=SHR
//SYSUT1 DD SPACE=(CYL,(3,3)),UNIT=(SYSDA,SEP=SYSPRINT)
//SYSUT2 DD SPACE=(CYL,(3,3)),UNIT=(SYSDA,SEP=(SYSPRINT,SYSUT1))
               UNIT=(SYSDA,SEP=(SYSUT2,SYSUT1,SYSLIB)),
//SYSUT3 DD
               SPACE=(CYL,(3,4))
"
//SYSGO DO
               UNIT=SYSDA.DSNAME=&LOADSET.SPACE=(CYL.(1.1)).DISP=(MUD.
                PASS)
11
//LKED
         EXEC
               PGM=IEWL, PARM=(XREF, LIST, LET), COND=(8, LT, ASM)
//SYSPRINT DD SYSOUT=A, DCB=(LRECL=121, RECFM=FBM, BLKSIZE=363, BUFNO=9)
               DSNAME=&TEMP(PDS), UNIT=SYSDA, SPACE=(CYL, (1,1,1)),
//SYSLMOD DD
                                                                            0030000
               DISP=(MOD, PASS)
11
//SYSLIB DD
               DSNAME=SYS1.LINKLIB.DISP=SHR
11
         DD
               DSNAME=HUM1.SUBRTLIB,DISP=SHR
11
         DD
               DSN=IMP1.SUBRTLIB,DISP=SHR
//SYSLIN DO
                                                                            0024000
               DSNAME=&LOADSET, DISP=(OLD, DELETE)
               DONAME=SYSIN
                                                                            0026000
11
         DD
               UNIT=(SYSDA, SEP=(SYSLIN, SYSLMOD)),
                                                                           2
//SYSUT1 DD
                SPACE=(CYL,(1,1))
```

```
MEMBER NAME #ASMFCZ
         PROC
                NAME=TEMP
                PGM=IEUASM, PARM= "NODECK, LOAD, XREF", TIME=20
//ASM
         EXEC
                DSN=IMP1.ZMACRO, DISP=SHR
//SYSLIB DD
                DSN=SYS1.MACLIB,DISP=SHR
         DD
                SYSOUT =A,DCB=(LRECL=121,RECFM=FBM,BLKSIZE=363,BUFNO=5)
//SYSPRINT DD
                SPACE=(CYL,(3,3)),UNIT=(SYSDA,SEP=SYSPRINT)
//SYSUT1 DD
                SPACE=(CYL, (3,3)), UNIT=(SYSDA, SEP=(SYSPRINT, SYSUT1))
//SYSUT2 DD
//SYSUT3 DD
                SPACE=(CYL,(3,3)),UNIT=(SYSDA,
                SEP=(SYSUT2.SYSUT1.SYSLIB))
11
                DISP=OLD, DSN= IMP1. ZOBJ (ENAME)
//SYSGO
         DD
```

```
MEMBER NAME #ASMFCLG
         EXEC
               PGM=IEUASM, PARM='NODECK, LOAD', TIME=10
//ASM
//SYSPRINT DD SYSOUT=A,DCB=(LRECL=121,RECFM=FBM,BLKSIZE=363,BUFNO=9)
//SYSLIB DD
               DSNAME=IMP1.ZMACRO, DISP=SHR
               DSNAME=SYS1.MACLIB, DISP=SHR
         OO
//SYSUT1 DD SPACE=(CYL,(3,3)),UNIT=(SYSDA,SEP=SYSPRINT)
//SYSUT2 DD SPACE=(CYL,(3,3)),UNIT=(SYSDA,SEP=(SYSPRINT,SYSUT1))
                UNIT=(SYSDA,SEP=(SYSUT2,SYSUT1,SYSLIB)),
//SYSUT3 DD
                SPACE=(CYL,(3,4))
//SYSGO
         00
                DSNAME=&LOADSET, UNIT=SYSDA, SPACE=(CYL, (1, 1)),
                                                                             0018000
11
                DISP=(MOD, PASS)
               PGM=IEWL, PARM=(XREF, LET, LIST), COND=(8, LT, ASM)
//LKED
         EXEC
//SYSPRINT DD SYSOUT=A,DCB=(LRECL=121,RECFM=FBM,BLKSIZE=363,BUFNO=9)
                DSNAME=&GOSET(GO), UNIT=SYSDA, SPACE=(CYL, (1,1,1)),
//SYSLMOD DD
                                                                             0030000
                DISP=(MOD. PASS)
11
//SYSLIB DD
                DSNAME=SYS1.LINKLIB.DISP=SHR
11
         DD
                DSNAME=HUM1.SUBRTLIB.DISP=SHR
                DSN=IMP1.SUBRTLIB.DISP=SHR
11
         00
                DSNAME = & LOADSET , DISP=(OLD. DELETE)
                                                                             0024000
//SYSLIN DD
                                                                             0026000
         nn
                DONAME = SYSIN
11
                UNIT=(SYSDA, SEP=(SYSLIN, SYSLMOD));
                                                                            20032000
//SYSUTI DD
                SPACE=(CYL,(1,1))
                                                                             0038000
//G0
         EXEC
               PGM= *. LKED . SYSLMOD
//SYSPRINT
            OD SYSOUT = A
//SYSUDUMP DD SYSOUT=A
```

```
MEMBER NAME #ASMFCLT
           PROC NAME=TEMP
11
//ASM
                  PGM= [EUASM, PARM= (NODECK, LOAD, XREF), TIME=10
           EXEC
//SYSPRINT DD SYSOUT=A,DCB=(RECFM=FBM,LRECL=121,BLKSIZE=363,BUFNO=9)
//SYSLIB
           DD DSN=IMP1.ZMACRO,DISP=SHR
"
           DD DSN=SYS1.MACLIB,DISP=SHR
//SYSUT1
           DD SPACE=(CYL, (3,3)), UNIT=(SYSDA, SEP=SYSPRINT)
//SYSUT2
           DD SPACE=(CYL,(3,3)),UNIT=(SYSDA,SEP=(SYSPRINT,SYSUTI))
//SYSUT3
           DD UNIT=(SYSDA,SEP=(SYSUT2,SYSUT1,SYSLIB)),
              SPACE=(CYL,(3,4))
11
//SYSGO
           DD DSN=&&LOADSET.UNIT=SYSDA.SPACE=(CYL,(1,1)),
11
              DISP=(MOD, PASS)
//LKED
           EXEC
                  PGM=IEWL,PARM=(XREF,LIST,LET),COND=(0,NE,ASM)
//SYSPRINT DD SYSOUT=A,DCB=(RECFM=FBM,LRECL=121,BLKSIZE=363,BUFNO=9)
//SYSLMOD
           DD DSN=&&GOSET(&NAME),UNIT=SYSDA, SPACE=(CYL,(1,1,1)),
              DISP=(MOD, PASS)
11
//SYSLIB
           DD DUMMY
           DD DSN=&&LOADSET, DISP=(OLD, DELETE)
//SYSLIN
//SYSUT1
           DD UNIT=SYSDA, SPACE=(CYL, (1,1))
//LOAD
                  PGM=TLOAD, PARM=(&NAME), COND=(0, NE, ASM)
           EXEC
//STEPLIB
           DD DSN=IMP1.DATALIB.UNDERHIL.DISP=SHR
//INPUT
           DD DSN=&&GOSET, DISP=(OLD, DELETE)
//OUTPUT
           DD DSN=IMP1.TFILE.DISP=SHR
//SYSUDUMP DD SYSOUT=A
```

```
MEMBER NAME MOVE
         PROC
                SER1=USRLIB, SER2=USRLIB, SER3=USRLIB, SER4=USRLIB
//MOVE
         EXEC
                PGM= IEHMOVE
//SYSPRINT DD
                SYSOUT=A
//SYSUT1 DD
                UNIT=2314,DISP=OLD,VOL=SER=USRLIB
1/11
         DD
                UNIT=2314, VOL=SER=&SER1, DISP=OLD
1/12
         DD
                UNIT=2314, VOL=SER=&SER2, DISP=OLD
//V3
         DD
                UNIT=2314, VOL=SER=& SER3, DISP=OLD
1144
         DD
                UNIT=2314, VOL =SER=&SER4, DISP=OLD
```

```
MEMBER NAME COMPRESS

// PROC ON=

//COMPRESS EXEC PGM=IEBCOPY

//SYSPRINT DD SYSOUT=A

//INPUT DD &ON,DSN=&PDS,DISP=OLD,UNIT=2314

//SYSIN DD DSN=HUM1.PC SLIB(COPY),DISP=SHR

//SYSUT3 DD UNIT=DISK,SPACE=(TRK,(1,25))

//SYSUT4 DD UNIT=DISK,SPACE=(TRK,(1,25))
```

```
MEMBER NAME PDSMOD

//*

//* UPDATE PARTITIONED DATASET

//*

// EXEC PGM=IMAPDSMD

//SYSPRINT DD SYSOUT=A,DCB=(LRECL=133,BLKSIZE=399,RECFM=FBA)

//SYSLIB DD DSNAME=&PDS,DISP=OLD
```

```
MEMBER NAME RORZ
         PROC
               LIB="IMP1.ZSOURCE", MBR=ZREG
                                                                           0000001
                                                                           0000002
//IEFPROC EXEC PGM=IEFIRC, PARM= 805030040010249070015YSDA
               DSNAME=&LIB.(&MBR),DISP=SHR
                                                                           0000003
//IEFRUER DU
//IEFPDSI DD
                                                                           0000004
               DSNAME=SYS1.PROCLIB,DISP=SHR
                                                                          20000005
//IEFDATA DU
               UNIT=SYSDA, SPACE=(80, (5, 100), RLSE, CONTIG),
               DCB=(LRECL=80,BUFNO=2,BLKSIZE=800,RECFM=FB,BUFL=800)
                                                                           0000006
                                                                           0000007
//SYSABEND DD SYSOUT=A, SPACE=(CYL, (10, 10))
```

MEMBER NAME	RGET	
//R	EXEC	PGM=RGETPUT,PARM="OUT,&LOGON"
//STEPLIB	00	DSN=IMP1.DATALIB.UNDERHIL.DISP=SHR
//SYSPRINT	DD	SYSOUT=A,DCB=(RECFM=F,BLKSIZE=100)
//SYSUDUMP	00	SYSOUT=A
//RFILE	DD	DSN=IMP1.RFILE,DISP=SHR

MEMBER NAME	RPUT	
11	PROC	LOGUN=TEMP
11K	EXEC	PGM=RGETPUT,PARM='IN, &LOGON'
//STEPLIB	00	DSN=IMP1.DATALIB.UNDERHIL,DISP=SHR
//SYSPRINT	OD	SYSOUT=A,DCB=(RECFM=F,BLKSIZE=100)
//SYSUDUMP	00	SYSOUT=A
//RFILE	DD	DSN=IMP1.RFILE,DISP=SHR

MEMBER NAME UT
//UT EXEC PGM=IMAPTPCH
//SYSPRINT DD SYSOUT=A, DCB=(LRECL=133, RECFM=FBA, BLKSIZE=399)
//SYSPUNCH DD SYSOUT=B, DCB=(LRECL=80, BLKSIZE=240, RECFM=FB)

```
MEMBER NAME ZEUS
         PROC
               PROG=STUDMODE, LIB= 'IMP1. PROGLIB'
//ZEUS
         EXEC
               PGM=&PROG, TIME=1000
//STEPLIB DD
               DISP=SHR,DSN=&LIB
//CRTLO
        DD
               UNIT=050 720 CRT LINE 1
               UNIT=051 720 CRT LINE 2
//CRTL1
         DD
               UNIT=053 720 CRT LINE 4
//CRTL3
        DD
//DUMMY DD
               UNIT =AFF=CRTLO DUMMY TP LINE
               DSNAME=CAIL.DFILEV3,DISP=SHR
//FILED DD
//FILEF DD
               DSNAME = CAII. FFILEV3, DISP = SHR
//FILEI DD
               DSNAME=CAIL.IFILEVI,DISP=SHR
//FILEQ DD
               DSNAME=CAIL-QFILEV3, DISP=SHR
//FILER DD DSN=IMP1.RFILE, DISP=SHR
//TFILE DD DSN=IMP1.TFILE,DISP=SHR
//SUBRFL DD
               DISP=SHR, DSN=CAI2. SRFILE
//SYSO10 DD DSN=CAI1.SYSO10,DISP=SHR
//SYSO11 DD UNIT=2314,DSN=CAI2.SYSO11,DISP=SHR
//SYS012 DD
             DSNAME=CAIL.SYSO12,DISP=SHR
//SYS020 DD
               DISP=SHR, DSN=CAI2.SYSO20
//SYS021 DD
               DISP=SHR,DSN=CAI2.SYS021
//SYS022 DD
               DISP=SHR,DSN=CAI2.SYS022
//LDAFLE DD
               DISP=SHR.DSN=CAI2.CAILDA
//SYSLST DD SYSOUT=A, UNIT=SYSOUT
//D1050C DD
               UNIT=AFF=DUMMY
       UNIT=AFF=DUMMY
// DD
        UNIT=AFF=DUMMY
11
   00
    DD
        UNIT=AFF=DUMMY
11
11
         OO
               UNIT=AFF=DUMMY
11
         DD
               UNIT=AFF=DUMMY
11
         DD
               UNIT=AFF=DUMMY
11
         DD
               UNIT=AFF=DUMMY
         DD
               UNIT = AFF = DUMMY
11
//ZLINE1 DD
               UNIT=AFF=CRTLO
              UNIT=AFF=CRTL1
        DD
11
        DD
              UNIT=AFF=CRTL3
11
//SYSUDUMP DD SYSOUT=F,UNIT=SYSOUT
//RJEFILE DD DSNAME=IMP1.RJEFILE,DISP=SHR
11*
//* THE FOLLOWING 3 DD CARDS ARE REQUIRED ONLY IF THE ZEUS WRITER
//*TASK IS TO BE MADE ACTIVE
//SYSWTR1 DD DSN=SYS1.POSTFILE,DISP=SHR
//SYSWTR2 DD DSN=SYS1.WTRSPOOL,DISP=SHR,DCB=RECFM=U
//SYSWTR3 DD UNIT=OOE, DCB=(RECFM=UM, BLKSIZE=133)
```

MEMBER NAME ZOLD

//IMPONL JOB (253A,IMPONL,O), OLD ZEUS, CLASS=M, MSGLEVEL=1

// EXEC ZEUS, PROG=STUDMODF, PARM=CWV210BJ

//SYSIN DD +,DCB=BLKSIZE=80

(10,11,9), (7,8,6), (4,5,3), ALLOCATE=8800

MEMBER NAME ZREG
//IMPONL JOB (253A, IMPONL, 0), "CURRENT ZEUS", CLASS=M, MSGLEVEL=1
// EXEC ZEUS, PARM=CWV210BJ, PROG=STUDMODE
//SYSIN DD *, DCB=BLKS IZE=80
(10,11,9), (7,8,6), (4,5,3), ALLOCATE=8800

MEMBER NAME ZTEST

//IMPONL JOB (253A, IMPONL, 0), "NEW ZEUS", CLASS=M, MSGLEVEL=1

// EXEC ZEUS, PROG=TESTMODE, LIB= "SYS1. GARNEAU", PARM=CWV210BJ

//SYSIN DD *, DCB=BLKSIZE=80

(10, 11, 9), (7, 8, 6), (4, 5, 3), ALLOCATE=8800